

z/OS
3.2

*Data Set File System Messages and
Codes*



Note

Before using this information and the product it supports, read the information in [“Notices” on page 119.](#)

This edition applies to IBM® z/OS® 3.2 (5655-ZOS) and to all subsequent releases and modifications until otherwise indicated in new editions.

Last updated: 2025-09-30

© **Copyright International Business Machines Corporation 2022, 2025.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

About this document.....	v
How to provide feedback to IBM.....	vii
Summary of changes.....	ix
Chapter 1. Introduction to DSFS Messages and Codes.....	1
Chapter 2. Messages.....	3
Chapter 3. Reason codes.....	85
Appendix A. Accessibility.....	117
Notices.....	119
Index.....	123

About this document

The purpose of this document is to provide complete and detailed guidance and reference information. This information is used by system administrators who work with z/OS Data Set File System (DSFS).

z/OS information

This information explains how z/OS references information in other documents and on the web.

When possible, this information uses cross-document links that go directly to the topic in reference using shortened versions of the document title. For complete titles and order numbers of the documents for all products that are part of z/OS, see *z/OS Information Roadmap*.

How to provide feedback to IBM

We welcome any feedback that you have, including comments on the clarity, accuracy, or completeness of the information. For more information, see [How to send feedback to IBM](#).

Summary of changes

This information includes terminology, maintenance, and editorial changes. Technical changes or additions to the text and illustrations for the current edition are indicated by a vertical line to the left of the change.

Note: IBM z/OS policy for the integration of service information into the z/OS product documentation library is documented on the z/OS Internet Library under [IBM z/OS Product Documentation Update Policy](http://www.ibm.com/docs/en/zos/latest?topic=zos-product-documentation-update-policy) (www.ibm.com/docs/en/zos/latest?topic=zos-product-documentation-update-policy).

Summary of changes for z/OS 3.2

There are no messages updates for z/OS 3.2.

Summary of changes for z/OS 3.1

The following messages are new, changed, or no longer issued for z/OS Data Set File System Messages and Codes in z/OS 3.1.

New messages

The following messages are new.

IDFS00370I
IDFS00371I
IDFS00372E
IDFS00373E

Changed messages

The following messages are changed.

IDFS00339E
IDFS00340E
IDFS00341E
IDFS00342E
IDFS00343E
IDFS00344E
IDFS00345E
IDFS00346E
IDFS00370I

No longer issued messages

The following messages are no longer issued.

IDFS00338

Changed reason codes

6221

Chapter 1. Introduction to DSFS Messages and Codes

Detailed explanations and recovery actions are provided to supplement the messages that are issued by Data Set File System (DSFS). Processing options that can be used to control DSFS are documented in [z/OS Data Set File System Administration](#).

Where to find the most current message information

In the z/OS library, as messages are added to the system, they are added to the documents. Similarly, when messages are changed on the system, they are changed in the documents. However, when a message is deleted from the system because they are no longer issued, the message is not deleted from the documents.

To find the most current description of a message, see [IBM Documentation \(www.ibm.com/docs/en/zos\)](http://www.ibm.com/docs/en/zos).

Understanding DSFS messages

Messages are divided into three categories: action, error, and informational. Those of the form IOEZnnnnnt are issued by DSFS, while messages prefixed with IOEZHnnnnnt are issued from the DSFS health checker.

The last part of the message number (*t*) is a single-character operator code that represents the type of recovery action to be taken by the operator in response to the message. These operator codes are associated with the different levels of severity, as listed in [“Severity levels” on page 1](#). The recovery actions are represented by the following characters:

A

Indicates that the operator must take immediate action, for example, recovering from a system failure.

D

Indicates that the operator must choose an alternative action, for example, responding yes or no.

E

Indicates that the operator must take eventual action, for example, loading paper in a printer.

I

Indicates that the message is informational and no action is required, for example, when a command completes successfully.

What is first-level message text?

Together, the message number and the message text that immediately follows the message number comprise the first-level text. This is the message information that is returned to the operator console or user display.

What is second-level message text?

The explanation and responses that supplement the message number and message text comprise the second-level text.

Severity levels

Each message contains a severity field that indicates the level of severity associated with the message. These severity levels are described in the following list:

svc_c_sev_fatal

Indicates a non-recoverable error that probably requires manual intervention. Usually, permanent loss or damage has occurred that results in the program terminating immediately, such as database corruption. Messages of this severity have an operator code of A.

svc_c_sev_error

Indicates that an unexpected event has occurred that does not terminate the program and which can be corrected by human intervention. The program continues although certain functions or services might remain unavailable. Examples include performance degradation that results in a loss of function, such as a timeout, or a specific request or action that cannot be completed, such as trying to add an object to a directory system when the object already exists. Messages of this severity have an operator code of A or E.

svc_s_sev_user

Indicates that a usage error on a public API has occurred, such as a syntax error. Messages of this severity have an operator code of A or E.

svc_c_sev_warning

Indicates one of the following conditions; messages of this severity have an operator code of E or I.

- An error occurred that was automatically corrected by the program or system. An example of an error corrected by a program is when a configuration file is not found during configuration and a message is issued warning the user that certain internal defaults were used.
- A condition has been detected which may be an error depending on whether the effects of the condition are acceptable. For example, a directory is deleted and a warning message is issued that all files contained in the directory will also be deleted.
- A condition exists that, if left uncorrected, will eventually result in an error.

svc_c_sev_notice

Indicates major events, such as the start of a server, completion of server initialization, or an offline server. Messages of this severity have an operator code of E or I.

svc_sev_notice_verbose

Indicates events of special interest, such as statistical information, key data values, use of default settings, and version information. However, it does not indicate program flow or normal events. Messages of this severity have an operator code of I.

Setting slip traps to obtain diagnosis data

When you receive a DSFS reason code and need additional diagnosis information, IBM Support Center might ask you set a slip trap to collect a dump when you recreate the problem.

As a general example, you can perform the following steps to obtain a dump on a specific DSFS reason code:

1. Enter the following command to determine the ASID for the DSFS Physical File System:

```
D A,DSFS
```

2. Look for the ASID of the DSFS address space in A=nnnn.
3. Use the following SLIP command to produce a dump when a specific reason code is issued:

```
SLIP SET,IF,A=SYNCSVCD,RANGE=(10?+8C?+F0?+1F4?),
ASIDLST=(nnnn),DATA=(13R?+1b0,EQ,xxxxxxx),DSPNAME=('OMVS'.*),
SDATA=(ALLNUC,PSA,CSA,LPA,TRT,SQA,RGN,SUM),j=jobname,END
```

nnnn

The DSFS ASID

xxxxxxx

The 4-byte DSFS reason code to trap.

jobname

The optional job name that is expected to issue the error (for example, j=IBMUSER).

Chapter 2. Messages

The following messages may result from DSFS processing.

IDFS00001E	DSFS I/O error <i>error_code</i> occurred for utility file system <i>file_name</i>.
-------------------	--

Explanation

A physical I/O error occurred on utility file system *file_name*. Additional messages are provided that give more information about the error.

error_code

The VSAM error code.

file_name

The utility file system name.

System action

The program continues.

Administrator response

Determine if there is a real hardware error. If there is, then take steps to correct the problem. Otherwise, contact your service representative.

IDFS00002E	MMRE error id=<i>IO_id</i> cis=<i>control_intervals</i> if=<i>input_flags</i> of=<i>output_flags</i> buf=<i>buffer_address</i> CI=<i>interval_number</i>.
-------------------	--

Explanation

This message documents additional information about a physical I/O error that occurred on a DSFS utility file system. This information is intended for IBM service personnel, and is used to provide more information on the details of the I/O error.

IO_id

The I/O ID indicating direction.

control_intervals

The number of control intervals involved.

input_flags

The Media Manager input flags.

output_flags

The Media Manager output flags.

buffer_address

The DSFS buffer address.

interval_number

The starting control interval number.

System action

The program continues.

Administrator response

Determine whether there is a real hardware error. If there is, then take steps to correct the problem. Otherwise, contact your service representative.

IDFS00003I Primary extent loaded successfully for *file_name*.

Explanation

The device driver has finished loading the primary extent of the named utility file system.

file_name

Name of the utility file system.

System action

The program continues.

IDFS00004A DSFS kernel unable to be set up to receive operator commands.

Explanation

The program was not able to be set up to receive MODIFY commands from the operator.

System action

The program continues.

Administrator response

Contact your service representative.

IDFS00005E *program_name*: Unable to open debug parameter data set *file_name*.

Explanation

The *program_name* program was not able to open the DSFS debug parameter data set. Default values will be used for DSFS debugging parameters.

program_name

The program name.

file_name

The parameter file name.

System action

The program continues.

Administrator response

Ensure that the *file_name* data set exists and that the *program_name* program has READ data set authority to it. If the problem continues, contact your service representative.

IDFS00006I *program_name*: Using default values for DSFS debug parameters.

Explanation

The *program_name* program is using default values for DSFS debug parameters.

program_name

The program name.

System action

The program continues.

Administrator response

None.

IDFS00007A *program_name: Incorrect parameter record line_error is ignored.*

Explanation

The *program_name* program found an incorrect record in the DSFS debug parameters data set.

program_name

The program name.

line_error

The line found to be in error.

System action

The program ends.

Administrator response

Correct the error and start *program_name* again.

IDFS00008A *program_name: Operand must be numeric (operand_name).*

Explanation

The *program_name* program found a nonnumeric value specified for a numeric operand.

program_name

The program name.

operand_name

The operand found to be in error.

System action

The program ends.

Administrator response

Specify a numeric value and start *program_name* again.

IDFS00009A *program_name: operand_name exceeds maximum value max_value.*

Explanation

The *program_name* program found a numeric operand that was too large.

program_name

The program name.

operand_name

The operand found to be in error.

max_value

The maximum value for the operand.

System action

The program ends.

Administrator response

Ensure that the operand *operand_name* is not larger than the *max_value* and restart *program_name*.

IDFS00010A *program_name: Operand must be string (operand_name).*

Explanation

The *program_name* program found a missing string operand.

program_name

The program name.

operand_name

The operand found to be in error.

System action

The program ends.

Administrator response

Ensure that the operand *operand_name* is specified and restart *program_name*.

IDFS00011A *program_name: operand_name exceeds max string length max_length.*

Explanation

The *program_name* program found a string operand that is too long.

program_name

The program name.

operand_name

The operand found to be in error.

max_length

The maximum length for the string.

System action

The program ends.

Administrator response

Ensure that the operand *operand_name* is not greater than *max_length* and restart *program_name*.

IDFS00012A *program_name: Partition start list operand_name not delimited by parentheses.*

Explanation

The *program_name* program found a syntax error in operand *operand_name* in the DSFS debug parameter data set.

program_name

The program name.

operand_name

The operand found to be in error.

System action

The program ends.

Administrator response

Ensure that the operand *operand_name* is delimited by parentheses and restart *program_name*.

IDFS00013I

***program_name*: Modify complete for *parameter_name* *parameter_value*.**

Explanation

The *program_name* program has successfully set the value of the program parameter *parameter_name* to *parameter_value*.

program_name

The program name.

parameter_name

The parameter name.

parameter_value

The parameter value.

System action

The program continues.

Administrator response

None.

IDFS00014A

***program_name*: Incorrect parameter debug record *record_name* in data set *dataset_name*.**

Explanation

The *program_name* found a syntax error in ioedebg record *record_name*.

program_name

The program name.

record_name

The record in error.

dataset_name

The data set name.

System action

The program ends.

Administrator response

Correct the error in the ioedebg record and restart *program_name*.

IDFS00015A

***program_name*: Incorrect parameter *parameter_name*.**

Explanation

The *program_name* found an incorrect parameter *parameter_name* in the DSFS debug parameters data set.

program_name

The program name.

parameter_name

The parameter in error.

System action

The program ends.

Administrator response

Specify a valid parameter and restart *program_name*.

IDFS00016E	<i>program_name</i>: Parameter <i>parameter_name</i> is not valid for modify command <i>command_name</i>.
-------------------	--

Explanation

The specified parameter *parameter_name* is not valid for the *parameter_name* command.

program_name

The program name.

command_name

The command in error.

parameter_name

The parameter in error

System action

The program continues.

Administrator response

Additional information about the syntax of the *command_name* command is found in *z/OS Data Set File System Administration*.

IDFS00017I	<i>program_name</i>: <i>product_name</i> <i>feature_name</i> Version <i>product_version</i>.<i>product_release</i>.<i>product_modlevel</i> Service Level <i>service_level</i>. Created on <i>creation_date</i>.
-------------------	--

Explanation

This message is issued when the level of DSFS is queried using the QUERY command. The system returns the product name, feature name, version, release, modification level, service level and creation date of the DSFS program.

program_name

The program name.

product_name

The product name.

feature_name

The feature name.

product_version

The product version.

product_release

The product release.

product_modlevel

The product modification level.

service_level

The product service level.

creation_date

The date and time the daemon was created.

System action

The program continues.

IDFS00018E *program_name: modify command is not valid - command_name.*

Explanation

The syntax of the modify command is not correct.

program_name

The program name.

command_name

The command name that is not valid.

System action

The program continues.

Administrator response

Additional information about the syntax of the *command_name* command is found in *z/OS Data Set File System Administration*.

IDFS00019E *program_name: MODIFY command - command_name failed.*

Explanation

The MODIFY command failed.

program_name

The program name.

command_name

The command name.

System action

The program continues.

Administrator response

Additional information about the syntax of the *command_name* command is found in *z/OS Data Set File System Administration*. Verify that the command was entered with valid parameters. If the problem continues, contact your service representative.

IDFS00020I *program_name: MODIFY command - command_name completed successfully.*

Explanation

The MODIFY command was successful.

program_name

The program name.

command_name

The command name.

System action

The program continues.

Administrator response

None.

IDFS00033I **Utility file system *file_name* attached successfully.**

Explanation

Utility file system *file_name* was successfully attached by DSFS.

file_name

Name of the utility file system.

System action

The program continues.

IDFS00034I **Detaching utility file system *file_name*.**

Explanation

Utility file system *file_name* is being detached.

file_name

Name of the utility file system.

System action

The program continues.

IDFS00035I ***program_name*: Stop command received.**

Explanation

The DSFS kernel has received an operator stop request. The utility file system will be detached and the DSFS kernel will terminate.

program_name

The DSFS program.

System action

The program continues.

IDFS00036I **An error occurred in program IDFFSKN.**

Explanation

The DSFS kernel encountered an internal error in program IDFFSKN. The DSFS kernel is being restarted.

program_name

The DSFS program.

System action

The program continues.

Administrator response:

Contact your service representative.

IDFS00037E **Error setting up termination thread, code = *error_code*.**

Explanation

An error occurred when the routine used to handle DSFS kernel termination was being defined. The result is that DSFS termination required by either an internal error or a command to shut down DSFS or the OMVS kernel will not function properly.

error_code

The error code.

System action

The program ends.

Administrator response:

Contact your service representative.

IDS00038E Error starting console thread, code = *error_code*.

Explanation

An error occurred during the attempt to start a thread to accept the operator MODIFY command. F DSFS commands will be disabled as a result.

error_code

The error code.

System action

The program ends.

Administrator response:

Contact your service representative.

IDS00039I DSFS kernel: initialization complete.

Explanation:

The DSFS kernel has completed initialization.

System action

The program continues.

IDS00040I DSFS kernel program IDFFSKN is ending.

Explanation:

The DSFS kernel program IDFFSKN has completed its termination processing and is about to end. It is normally restarted by the DSFS control program IDFFSCM.

System action

The program continues.

IDS00041A DSFS kernel: could not create admin thread, code *error_code*.

Explanation

A DSFS kernel could not create a thread to process administration commands.

error_code

The error code.

System action

The program ends.

Administrator response

Determine if enough storage is specified for the DSFS kernel. If increasing storage does not help the problem, contact your service representative.

IDFS00042I

General Registers *Register_number: register_value register_value
register_value register_value*

Explanation

A DSFS kernel was driven for recovery for a z/OS UNIX process. This message shows the registers at time of error.

register_number

The register number.

register_value

The value of a register.

register_value

The value of a register.

register_value

The value of a register.

register_value

The value of a register.

System action

The program continues.

Administrator response

This message will be followed by additional messages indicating more about the problem. Recovery may not be a problem.

IDFS00043E

DSFS utility file system *file_name* exceeds %%d%% full (%%u/%%u) (WARNING).

Explanation

A DSFS utility file system used space has exceeded the administrator defined threshold specified on the `fsfull` option.

file_name

Name of the utility file system.

System action

The program continues.

Administrator response

If desired, increase the utility file system size.

IDFS00044I

DSFS utility file system *file_name* is now below %%d%% full (%%u/%%u).

Explanation

A DSFS utility file system used space has fallen below the administrator defined threshold specified on the `fsfull` option.

file_name

The name of the DSFS utility file system.

System action

The program continues.

IDFS00045A **Signal *signal_type* received, dump in progress.****Explanation**

A DSFS program is abending, and a dump is in progress.

signal_type

The signal type.

System action

The system ends.

Administrator response

Contact your service representative.

IDFS00046A **DSFS: PSW from Machine State: *psw_part1* *psw_part2* Abend Code from CIB: *abend_code* Reason Code from CIB: *reason_code* Load Module Name: *module_name*****Explanation**

Abend information at time of dump.

psw_part1

First part of PSW.

psw_part2

Second part of PSW.

abend_code

Abend code information.

reason_code

Reason code information.

module_name

Module name that abended.

System action

The system ends.

Administrator response:

Contact your service representative.

IDFS00047A **Assertion Failed:*assertion* Line:*line_number* File:*file_name*.****Explanation**

An internal error has occurred in the dsadm program. A dump will be taken.

assertion

The assertion.

line_number

The line number.

file_name

The file name.

System action

The program ends.

Administrator response:

Contact your service representative.

IDFS00048E

Syntax error string *text_error* on line(s) *starting_line:ending_line* in configuration data set *file_name*.

Explanation

A syntax error was found while parsing the DSFS parameter data set. The line in error is shown as an aid to the administrator.

text_error

The text in error.

starting_line

The starting line number of the statement in error.

ending_line

The ending line number of statement in error.

file_name

The configuration file name.

System action

The program continues.

Administrator response:

Correct the line in error and retry the operation.

IDFS00049E

The configuration data set *file_name* could not be opened.

Explanation

Since DSFS could not open the data set, it will continue without one and will use defaults for all configuration options.

file_name

The configuration file name.

System action

The program continues.

Administrator response:

Look for related error messages in the system log to determine why the open failed. Ensure that the DSFS configuration data set is accessible to the program and retry the operation.

IDFS00050E

The parameter, *parameter_name*, requires *string* non-null argument value.

Explanation

The parameter requires one or more values, but none were specified.

parameter_name

The parameter name.

string

The string 'a' or 'at least one'.

System action

The system ends.

User response:

Enter the command specifying a value for *string*.

IDFS00051E

The argument, *argument*, does not represent a valid value for the parameter *parameter_name*.

Explanation

The value specified for the parameter was not valid.

argument

The argument.

parameter_name

The parameter name.

System action

The system ends.

User response:

Enter the command with a valid value for the parameter.

IDFS00052E

The user is not authorized to run this command.

Explanation:

This command requires a uid of 0, or READ access to the SUPERUSER.FILESYS.PFCTL profile in the UNIXPRIV class.

System action

The system ends.

IDFS00054E

Open error on file(*dataset_name*), errno(*return_code*).

Explanation

An error occurred opening the messages data set pointed to by *msg_input_dsn* in the configuration data set.

dataset_name

Data set name pointed to by configuration parameter *msg_input_dsn*.

return_code

Return code from open.

System action

The program continues. Messages will be from the in core message table.

Administrator response:

Check the *msg_input_dsn* variable in the configuration data set and verify that the messages data set exists.

IDFS00055E

Read error on file(*dataset_name*), errno(*return_code*).

Explanation

An error occurred reading the messages data set pointed to by *msg_input_dsn* in the configuration data set.

dataset_name

Data set name pointed to by configuration parameter `msg_input_dsn`.

return_code

Return code from open.

System action

The program continues. Messages will be from the in-core message table.

Administrator response:

Check the `msg_input_dsn` variable in the configuration data set and verify that the messages data set exists.

IDFS00056E**Insufficient storage available.****Explanation:**

An error occurred attempting to allocate storage.

System action

The program continues. Messaging may not occur.

Administrator response:

Check that the task was started with sufficient storage.

IDFS00057E**Unable to retrieve message text for message ID(*message_number*).****Explanation**

An error occurred while trying to retrieve message text for the displayed message ID. The message number that was being displayed is reported.

message_number

The message number of text that the task was attempting to retrieve.

System action

The program continues. Messaging may not occur.

Administrator response:

Task may need to be restarted to correct the messaging control block.

IDFS00058E**Unknown message.****Explanation:**

An error occurred while trying to retrieve message text for the displayed message ID. This message ID is unknown to the task.

System action

The program continues. Messaging may not occur.

Administrator response:

Task may need to be restarted to correct the messaging control block.

IDFS00062E**Open of utility file system *filesystem_name* failed with rc *return_code*.****Explanation**

In order to quiesce file system *filesystem_name*, it needs to be opened. This operation failed with a return code of *return_code*. Therefore, the utility file system is not quiesced.

filesystem_name

The utility file system name.

return_code

The return code received.

System action

The program continues.

Administrator response:

Use the return code to determine why the open failed. If the return code is EIO (122) then this message is likely preceded by messages that indicate the reason for the disk IO failure. If the return code is EMVSERR (157) then contact IBM service. Correct the problem and try the operation causing the quiesce again.

IDFS00064I

***dataset_name* is the configuration data set currently in use.**

Explanation

This message notifies the user of the configuration data set in use.

dataset_name

The configuration data set name.

System action

The program continues.

Administrator response:

None.

IDFS00065E

Could not open trace output data set.

Explanation:

A DSFS program could not print the in-memory trace table.

System action

The program continues.

Administrator response:

Ensure that the data set that should contain the trace exists, is writable, and is not allocated to another job or user.

IDFS00066E

Could not write to trace output data set.

Explanation:

A DSFS program could not print the in-memory trace table.

System action

The program continues.

Administrator response:

Ensure that the data set that should contain the trace exists, is writable, and is not allocated to another job or user.

IDFS00069E

**DASD volser *volume_serial_name* is offline, utility file system
utility_filename cannot be mounted.**

Explanation

A utility file system was being mounted and DSFS detected that the utility file system is on a DASD volume that is offline.

volume_serial_name

The DASD volume serial name.

utility_filename

The utility file system name that was being mounted.

System action

The program continues.

Administrator response:

Ensure the specified DASD volume is online and remount the utility file system.

IDFS00070E

Error return_code reason reason_code encountered obtaining status on volser serial_name for utility file system utility_file_name, macro macro_name.

Explanation

A utility file system was being attached and DSFS could not obtain information via the *macro_name* macro on the DASD volser shown in the message.

return_code

The UCBINFO macro return code.

reason_code

The UCBINFO macro reason code.

serial_name

The DASD volume serial name.

utility_file_name

The utility file system name of a prior attached utility file system name.

macro_name

The macro name.

System action

The program continues.

Administrator response:

Check the z/OS documentation on the *macro_name* macro to determine the source of the error. If the problem continues, contact your service representative.

IDFS00071I

Access Registers ARregister_number: register_value register_value register_value register_value

Explanation

A DSFS kernel was driven for recovery for a z/OS UNIX process. This message shows the access registers at time of error.

register_number

The register number.

register_value

The value of a register.

System action

The program continues.

Administrator response:

This message will be followed by additional messages indicating more about the problem. Often, recovery is not a problem.

IDFS00072A

DSFS kernel out of storage, total of megabytes bytes used, size attempted was storage, class class_number type storage_type.

Explanation

The DSFS kernel ran out of storage when attempting to obtain *storage* bytes. *megabytes* is the number of bytes that has been obtained by the DSFS kernel. *class_number* and *storage_type* is information for IBM service personnel.

megabytes

The total number of megabytes used by DSFS.

storage

The amount of storage that DSFS attempted to obtain.

class_number

The DSFS kernel sub-component class number.

storage_type

The storage type of the DSFS kernel.

System action

The program ends.

System action:

Try restarting DSFS with smaller cache sizes. This message is followed by output showing the DSFS kernel storage map. If problem continues, contact your service representative.

IDFS00076I

***program_name* Commands are:**

Explanation

When the *help* subcommand parameter is the only argument supplied for a command, a list of the valid subcommands is returned.

program_name

The program name.

System action

The program ends.

IDFS00077I

***program_name* Unknown topic *subcommand_name*.**

Explanation

The parameter is not a valid subcommand for this command.

program_name

The program name.

subcommand_name

The subcommand name.

System action

The program ends.

User response:

Enter the command again specifying a valid subcommand name.

IDFS00078I

***program_name* Ambiguous topic *subcommand_name*; use 'apropos' to list.**

Explanation

The parameter is ambiguous for *subcommand_name* because more than one subcommand or topic can match the string. Use **apropos** to list them.

program_name

The program name.

subcommand_name

The subcommand name.

System action

The program ends.

User response:

Enter the command again using an appropriate topic that is not abbreviated.

IDFS00079I

***program_name1*: Type '*program_name2*' for help.**

Explanation

The *program_name* command was entered without an argument; at least one is required.

program_name1

The program name.

program_name2

The program name.

System action

The program ends.

User response:

Enter the command again with one or more arguments.

IDFS00080I

***program_name1*: Type '*program_name2* help' or '*program_name3* help -topic <*command_name* ...>' for help.**

Explanation

The *program_name1* command suite was entered without the required command name.

program_name1

The program name.

program_name2

The program name.

program_name3

The program name.

System action

The program ends.

User response:

Enter the command suite again specifying an appropriate command name.

IDFS00081I

***status* operation *subcommand_name*; type '*program_name* help' for list.**

Explanation

The subcommand *subcommand_name* is either ambiguous or not valid. Commands cannot be abbreviated because multiple subcommands might match the abbreviation. Type *program_name* help for a list of valid subcommands.

status

Either the word 'Unknown' or the word 'Ambiguous'.

subcommand_name

The invalid or ambiguous subcommand.

program_name

The program name.

System action

The program ends.

User response:

Enter the *program_name* command again specifying a valid, unabbreviated subcommand.

IDFS00082I

status operation subcommand_name; type 'program_name help' for list.

Explanation

The subcommand *subcommand_name* is either ambiguous or not valid. Commands cannot be abbreviated because multiple subcommands might match the abbreviation. Type *program_name -help* for a list of valid subcommands.

status

Either the word Unknown or the word Ambiguous.

subcommand_name

The invalid or ambiguous subcommand.

program_name

The program name.

System action

The program ends.

User response:

Enter the *program_name* command again specifying a valid, unabbreviated subcommand.

IDFS00083I

'program_name -help'

Explanation

The command was entered with a parameter that was ambiguous or not valid.

program_name

The program name.

System action

The program ends.

User response:

Enter the command again using a valid parameter.

IDFS00084I

'program_name subcommand_name -help'

Explanation

The parameter entered for the subcommand was ambiguous or not valid.

program_name

The program name.

subcommand_name

The subcommand name.

System action

The program ends.

User response:

Enter the subcommand with a valid parameter.

IDFS00085I *program_name* Too many arguments.

Explanation

Too many arguments were entered for the *program_name* command.

program_name

The program name.

System action

The program ends.

User response:

Enter the command again specifying fewer arguments.

IDFS00086I *program_name* Too many values after parameter *parameter_name*.

Explanation

Too many values were entered for parameter *parameter_name*. *parameter_name* is a single-valued parameter and more than one value was provided on the command line.

program_name

The program name.

parameter_name

The parameter name.

System action

The program ends.

User response:

Enter the command with only one value for the *parameter_name* parameter.

IDFS00087E *program_name* Missing required parameter *parameter_name*.

Explanation

A required parameter for this command was not entered.

program_name

The program name.

parameter_name

The parameter name.

System action

The program ends.

User response:

Enter the command specifying a value for the required parameter.

IDFS00088I *program_name* status switch *switch_name*; type the following for detailed help.

Explanation

The switch name entered was either ambiguous, abbreviated, or an incorrect switch.

program_name

The program name.

status

The word 'Ambiguous' or the word 'Unrecognized'.

switch_name

The switch name.

System action

The program ends.

User response:

Enter the command with a valid, unabbreviated switch name.

IDFS00089I **The parameters *parameter1* and *parameter2* cannot be used together.**

Explanation

The parameters *parameter1* and *parameter2* are mutually exclusive, both cannot be specified on same command line.

parameter1

The parameter name.

parameter2

The parameter name.

System action

The program ends.

User response:

Enter the command with a valid, unabbreviated switch name.

IDFS00090I **Usage: *program_name**subcommand_name*.**

Explanation

This message displays the command syntax when the -help parameter is entered.

program_name

The program name.

subcommand_name

The subcommand name.

System action

The program ends.

User response:

None.

IDFS00091E ***string_type* *string_error* is longer than the maximum length of *maximum_length*.**

Explanation

The specified string is too long.

string_type

Type of string.

string_error

The string in error.

maximum_length

The maximum length.

System action

The program continues.

Administrator response:

Correct the string in error and retry the operation.

IDFS00093E

Could not set *admin_option* to *new_value*, error code *return_code* reason code *reason_code*.

Explanation

The DSFS kernel encountered an error while attempting to set the configuration option. In the case of the file cache, it could be that the user tried to fix the file cache via the EDCFIXED option past the current 14GB limit for DSFS DMA memory or there is not enough DMA memory on the system to satisfy the request. Message IDFS0093E will indicate which cache spaces could not be fixed in this case and the QUERY,FILECACHE command can be used to determine which cache spaces are fixed. In this latter case the file cache should be the requested size but not all cache spaces will be fixed.

admin_option

The administration option.

new_value

The new value.

return_code

The return code from the DSFS kernel.

reason_code

The reason code.

System action

The program continues.

Administrator response:

Consult *z/OS Data Set File System Messages and Codes* for the provided reason code, most likely a value was larger than the DSFS-defined maximum or smaller than the DSFS defined minimum for that option. If the command was a **config -filecache_size** command on a system that was using compression or the EDCFIXED option was specified on the command, check the amount of DMA memory available on your system and its usage by other applications and use the QUERY,FILECACHE command to determine which cache spaces are fixed by DSFS.

IDFS00094E

Utility file system *utility_name* failed dynamic grow, (by user *user_ID*).

Explanation

Dynamic growth of the specified utility file system, caused by the actions of the specified user, failed. All subsequent attempts to dynamically grow the utility file system will also fail. This condition can be changed by unmounting and remounting the utility file system. If the system is in a shared file system environment, a DSFS restart is required in order to remount the utility file system.

utility_name

The utility file system name.

user_ID

The user ID of the user causing the grow.

System action

The program continues.

Administrator response:

Determine if the failure code represents a problem. If so, and the problem persists, contact the service representative.

IDFS00095I	Utility file system <i>utility_name</i> successfully dynamically grown (by user <i>user_ID</i>).
-------------------	---

Explanation

Dynamic growth of the specified utility file system, caused by the actions of the specified user, was successful.

utility_name

The utility file system name.

user_ID

The user ID of the user causing the grow.

System action

The program continues.

Administrator response:

None.

IDFS00096I	Dynamic growth of utility file system <i>utility_name</i> in progress, (by user <i>user_ID</i>).
-------------------	---

Explanation

Dynamic growth of the specified utility file system, caused by the actions of the specified user, has been initiated. A subsequent message will be issued to indicate success or failure of this operation.

utility_name

The utility file system name.

user_ID

The user ID of the user causing the grow.

System action

The program continues.

Administrator response:

None.

IDFS00100E	No options have been specified.
-------------------	--

Explanation:

A **dsadm** command option has not been specified.

System action

The program ends.

Administrator response:

Specify a valid option for the command and retry.

IDFS00101E	Could not get value for <i>admin_option</i>, error code <i>return_code</i> reason code <i>reason_code</i>.
-------------------	---

Explanation

The DSFS kernel encountered an error while attempting to get the value of the configuration option.

admin_option

The administration option.

return_code

The return code from the DSFS kernel.

reason_code

The reason code.

System action

The program ends.

Administrator response:

Correct any problems and retry.

IDFS00103I	Attempting to extend <i>utility_name</i> to <i>new_size new_size</i> byte control intervals.
-------------------	---

Explanation

The utility file system is being extended to the indicated size.

utility_name

The utility file system name.

new_size

The new size for the data set.

interval_size

The control interval size of the utility file system.

System action

The program continues.

Administrator response:

None.

IDFS00104I	Formatting to <i>interval_size</i> byte control interval <i>new_count</i> for secondary extents of <i>utility_name</i>.
-------------------	--

Explanation

The utility file system has been extended into one or more secondary extents and one or more of those secondary extents is now being formatted, the data set will be the specified size when complete.

interval_size

The control interval size of the utility file system.

new_count

The new control interval count for the data set.

utility_name

The utility file system name.

System action

The program continues.

Administrator response:

None.

IDFS00105E	Error <i>return_code</i> formatting secondary extents for <i>utility_name</i>.
-------------------	---

Explanation

The attempt to format one or more secondary extents for the utility file system has failed, the Media Manager return code is shown.

return_code

The Media Manager return code.

utility_name

The utility file system name.

System action

The program continues.

Administrator response:

Verify that the data set exists and that the application can write to it.

IDFS00106E

Error *return_code* extending *utility_name*.

Explanation

The attempt to extend the utility file system has failed, the Media Manager return code is shown.

return_code

The Media Manager return code.

utility_name

The utility file system name.

System action

The program continues.

Administrator response:

Verify that the data set exists and that the application can write to it, ensure there is enough DASD space on the data sets associated DASD volumes for the data set to be grown.

IDFS00107I

Attempting to extend *utility_name* by a secondary extent.

Explanation

The utility file system is being extended by a secondary extent.

utility_name

The utility file system name.

System action

The program continues.

Administrator response:

None.

IDFS00108A

File system type *file_type* is incorrect. It must be DSFS.

Explanation

An incorrect type for Data Set File System was specified in the BPXPRMxx FILESYSTYPE statement. This value must be the characters DSFS.

file_type

The type that is specified in the BPXPRMxx file.

System action

The program ends.

Administrator response:

Update the FILESYSTYPE statement and ensure the TYPE parameter specifies DSFS. For example: TYPE(DSFS).

IDFS00110I**Return code and reason code for dump is *code*.**

Explanation

This message shows the return code and reason code returned by SVC dump processing. In some circumstances, a dump can be suppressed by the operating system.

code

The return code and reason code.

System action

The program continues.

Administrator response:

None.

IDFS00111E**DSFS kernel: non-terminating exception *abend_code* occurred, reason *reason_code* abend psw *first_PSW* *second_PSW*.**

Explanation

A DSFS kernel encountered an exception. A dump will be issued and the internal trace table will be printed. This exception is non-terminating, the DSFS kernel will continue to run, though there may be errors encountered for a given data set. The abend code is *abend_code*, and the psw is given by *first_PSW* *second_PSW*.

abend_code

The abend code received.

reason_code

The reason code received.

first_PSW

The first word of the abend PSW.

second_PSW

The second word of the abend PSW.

System action

The program continues.

Administrator response:

This message will be followed by additional messages indicating more about the problem. Contact your service representative.

IDFS00112A**DSFS kernel: restarting exception *abend_code* occurred, reason *reason_code* abend psw *first_PSW* *second_PSW*.**

Explanation

The DSFS kernel encountered an exception. A dump will be issued. The DSFS kernel will be stopped and a restart requested from z/OS UNIX. If the restart is successful, the utility file system may be remounted. Files that are currently open may see IO errors. The abend code is *abend_code*, and the psw is given by *first_PSW* *second_PSW*. If z/OS UNIX cannot restart DSFS, the system will display a BPXF032D message that must be replied to for DSFS to reinitialize.

abend_code

The abend code received.

reason_code

The reason code received.

first_PSW

The first word of the abend PSW.

second_PSW

The second word of the abend PSW.

System action

The program continues.

Administrator response:

This message will be followed by additional messages indicating more about the problem. Ensure that the utility file system is remounted after DSFS restarts. Contact your service representative.

IDFS00113E

Potential DSFS hang detected. Taking informational dump.

Explanation:

The DSFS Physical File System detected at least one user task that has a request that has not been satisfied for approximately three minutes. DSFS considers this to be a potential hang and dumps the DSFS address space for diagnostic purposes.

System action

The program continues.

Administrator response:

Contact IBM Service personnel, and send the dump. If necessary, stop and restart DSFS.

IDFS00114E

dsadm query *query_name* failed, rc = *return_code*, reason = *reason_code*.

Explanation

The indicated **dsadm query** command failed. The return and reason codes may indicate the cause of the error. If possible correct the error and retry.

query_name

The query option name.

return_code

The return code.

reason_code

The reason code.

System action

The program continues.

Administrator response:

Correct any errors and retry the command.

IDFS00115E

The attempt to create the *daemon_name* daemon failed with return code *return_code*.

Explanation

The creation of a thread for the daemon failed. See *z/OS MVS Programming: Authorized Assembler Services Reference ALE-DYN* for additional information about the ATTACH macro and its return codes. In the message text:

daemon_name

The name of the daemon.

return_code

The MVS attach return code.

System action

The program continues.

Administrator response:

Determine why the thread could not be created by using the return code from the ATTACH macro. Correct the problem and restart DSFS. If the problem persists, contact your service representative.

IDFS00116E

Insufficient memory to allocate *number_bytes* bytes.

Explanation

An error occurred while attempting to allocate memory needed to process the command.

number_bytes

The number of bytes to be allocated.

System action

The request fails, and DSFS continues operating normally.

Administrator response:

Ensure that sufficient memory is available, then try the request again.

IDFS00117E

Error *error_code*, reason *reason_code* received opening parmlib.

Explanation

An error was received while attempting to open the parmlib. The error code from the IEFPRMLB macro is shown.

error_code

The error code from the IEFPRMLB macro.

reason_code

The reason code from the IEFPRMLB macro.

System action

The program continues.

Administrator response:

Ensure the parmlib is accessible to the program and retry the operation.

IDFS00118I

No IDFZPRM DD specified in *address_space* proc. Parmlib search being used.

Explanation

This message notifies the user that parmlib search is being used. *address_space* is the name of the address space where DSFS is running.

address_space

The address space name.

System action

The program continues.

Administrator response:

None.

IDFS00120E

Unrecoverable error encountered for inode *inode* uniquifier *uniquifier* representing *dataset_member*.

Explanation

A fatal error was encountered for an object with inode *inode*, which represents data set *dataset_member*. Future accesses to the data set (or member of the data set) may fail and updates may be lost. One possible cause of this is a member of a PDS that was being accessed by DSFS was deleted while DSFS did not hold the data set ENQs, and the application was still accessing it.

inode

The inode of object in error.

uniquifier

The uniquifier of the object in error.

dataset_member

The data set and member the object represents.

System action

The program continues.

Administrator response:

If the member still exists, contact your service representative.

IDFS00121I	Recovery statistics for <i>utility_name</i> elapsed time <i>elapsed_time</i> ms <i>pages</i> log <i>pages</i> <i>records</i> log records, <i>data_blocks</i> data blocks modified <i>redo_data</i> redo-data, <i>redo_fill</i> redo-fill records <i>redo_datafill</i> undo records, <i>blocks</i> unwritten blocks.
-------------------	--

Explanation

This message notifies the user that a utility file system underwent recovery. This is normal if the utility file system was not detached cleanly before a stop or an outage of DSFS.

utility_name

The utility file system name.

elapsed_time

The elapsed time in msec.

pages

The number of pages.

records

The number of records.

data_blocks

The number of data blocks.

redo_data

The number of redo data records.

redo_fill

The number of redo fill data records.

redo_datafill

The number of redo data plus fill records.

blocks

The number of blocks not updated due to reuse.

System action

The program continues.

Administrator response:

None.

IDFS00123I	<i>program_name</i> Option <i>option_name</i> has been processed. This specification is ignored.
-------------------	---

Explanation

The specified option was already processed. Because this option was either explicitly specified previously or implicitly assumed according to the option omission rules, it is ignored.

program_name

The program name.

option_name

The option.

System action

The program ends

Administrator response:

Enter the command with only one value for the option.

IDFS00129E

Syntax error string *text_error* on line(s) *start_line*:*end_line* in parmlib member(s) *first_suffix*:*last_suffix*.

Explanation

A syntax error was found while parsing the DSFS parmlib. The line in error is shown as an aid to the administrator.

text_error

The text in error.

start_line

The starting line number of the statement in error.

end_line

The ending line number of the statement in error.

first_suffix

The first parmlib member suffix.

last_suffix

The last parmlib member suffix.

System action

The program continues.

Administrator response:

Correct the line in error and retry the operation.

IDFS00130E

Insufficient memory to allocate *num_bytes* bytes.

Explanation

An error occurred while attempting to allocate memory needed to process the command.

num_bytes

The number of bytes

System action

The request fails, and DSFS continues operating normally.

Administrator response:

Allocate more storage and retry the request.

IDFS00131E

Utility file system *utility_name* disabled.

Explanation

An error was found while processing requests for the specified utility file system. As a result all reads and writes to the utility file system are prevented.

utility_name

The utility file system name.

System action

DSFS will attempt a restart, and if in a shared file system environment, an automatic re-mount of the utility file system.

Administrator response:

If there were reported IO errors perhaps due to lost connectivity to DASD or device failures, ensure that the hardware is working properly. If the BPXF032D message is issued, reply R to restart DSFS. Then, if the utility file system is not automatically remounted, remount the utility file system. If the utility file system is corrupted, it will automatically be reformatted during the mount. If this condition persists, contact your service representative.

IDFS00134E	Internal error, utility file system <i>utility_name</i> cannot be detached from DSFS.
-------------------	--

Explanation

An internal error was found while processing a request to detach the specified utility file system. The detach problem could not be internally fixed. The utility file system can no longer be detached and hence is unusable until DSFS is restarted.

utility_name

The utility file system name.

System action

DSFS will remain active until it is manually restarted. No utility file system will be able to be mounted or unmounted.

Administrator response:

DSFS will need to be restarted to clear this error condition. A dump will likely be obtained by DSFS, contact your service representative.

IDFS00137E	Disabling IO to DASD volume <i>volume_name</i>.
-------------------	--

Explanation

An internal error has forced DSFS to temporarily disable IO to a particular DASD volume. All queued IO is stopped with error and IO to the DASD volume remains suppressed until in-progress IO to the DASD volume completes. This message will normally be preceded by a dump to provide necessary service information. Once all in-progress IO completes, the DASD IO queue is re-initialized and future IOs will be allowed from that point in time.

volume_name

The name of the DASD volume.

System action

The program continues.

Administrator response:

Contact your service representative.

IDFS00138I	IO to DASD volume <i>volume_name</i> has been enabled.
-------------------	---

Explanation

An internal error had forced DSFS to temporarily disable IO to a particular DASD volume. The internal error state has been cleaned up and IO to the DASD volume is now allowed.

volume_name

The name of the DASD volume.

System action

The program continues.

Administrator response:

None.

IDFS00139I

Starting Query Command *query_name*.

Explanation

Starting to run a query command.

query_name

The name of the query being run.

System action

The program continues.

Administrator response:

None.

IDFS00143E

Error extending *utility_name* DFSMS return code = *return_code*, PDF code = *return_code*.

Explanation

The attempt to extend the utility file system has failed, the Media Manager return code and PDF code is shown. Refer to message IEC161I.

utility_name

The utility file system name.

return_code

The Media Manager return code.

return_code

The PDF return code.

System action

The program continues.

Administrator response:

Verify that the data set exists and that the application can write to it, ensure there is enough DASD space on the data sets associated DASD volumes for the data set to be grown.

IDFS00145I

DSFS does not support the stop command. Please issue *f omvs, stoppfs=dsfs*.

Explanation:

The stop command is not supported. Please issue the omvs stoppfs command.

System action

The program continues.

Administrator response:

Issue `f omvs,stopps=dsfs`.

IDFS00146I

DSFS has a potentially hanging thread caused by: *address_list*.

Explanation

The DSFS hang detector found a thread that could possibly be hanging.

address_list

A list of address space IDs and TCB addresses causing the hang.

System action

The program continues.

Administrator response:

Monitor the potential hang. You can issue `F DSFS,QUERY,THREADS` to see the thread states. If the problem persists, try canceling the listed address space IDs. If the problem persists, contact your service representative.

IDFS00148E

Media Manager return code *error_code* for utility file system *utility_name*.

Explanation

Media Manager return code was nonzero for the specified utility file system.

error_code

The hexadecimal error code from the Media Manager request.

utility_name

The utility file system name.

System action

The program continues.

Administrator response:

Look up the error in the Media Manager return codes section of *z/OS DFSMSdfp Diagnosis Reference*.

IDFS00149E

DSFS I/O timed out for utility file system *utility_name*.

Explanation

A physical I/O error occurred due to the IO needed to attach utility file system *utility_name* taking more than 4 minutes to complete.

utility_name

The utility file system name.

System action

The program continues.

Administrator response:

Determine if there is a real hardware error. If there is, then take steps to correct the problem. Otherwise, contact your service representative.

IDFS00150E

Utility file system ran out of space.

Explanation:

The utility file system ran out of space. DSFS will attempt to dynamically grow the utility file system. This message will appear at most once every ten minutes.

System action

The program continues.

Administrator response:

Ensure that there is sufficient space in the utility file system.

IDFS00151E

dsadm command failed, rc = `return_code`, reason = `reason_code`.

Explanation

The indicated **dsadm query** command failed. The return and reason codes may indicate the cause of the error. If possible correct the error and retry.

return_code

The return code.

reason_code

The reason code.

System action

The program continues.

Administrator response:

Correct any errors and retry the command.

IDFS00152E

An internal error occurred waiting for retry of a user task dump for asid `address_space`.

Explanation

DSFS attempted to take a dump of a user task in the address space mentioned. This dump failed for some reason, possibly due to the address space taking another dump or some other reason. In an attempt to get a dump, DSFS retries the SDUMPX call on a DSFS task. An internal error occurred attempting to wait for the DSFS task to complete. So, the dump may not be finished before the user task completes its DSFS request. Therefore, the dump may not prove to be useful in resolving the reason for dumping in the first place. At any rate, IBM service should be contacted.

address_space

The ID of the user task address space.

System action

The program continues.

Administrator response:

Contact IBM service.

IDFS00153I

***program_name: Initializing product_name feature_name Version
product_version.product release.mod_level Service Level service level.
Created on time_created. Address space asid asid.***

Explanation

This message is issued when the named DSFS program starts. It identifies the product name, feature name, version, release, modlevel, service level, creation date and asid of the DSFS program.

program_name

The program name.

product_name

The product name.

feature_name

The feature name.

product_version

The product version.

product release

The product release.

mod level

The modification level.

service level

The service level.

time created

The date and time the DSFS program was created.

asid

The asid of the address space.

System action

The program continues.

Administrator response

None.

IDFS00156E

The DSFS utility file system is quiesced.

Explanation:

The utility file system is quiesced. A quiesced utility file system can cause delays or slow performance for some tasks. This informational message is a debug aid only. When the utility file system is quiesced, this message will appear on the console highlighted. When the utility file system is no longer quiesced, the message will not be highlighted. Every 30 seconds a thread wakes up and determines whether the utility file system is quiesced. If it is, the thread will make sure that this message is on the console. If the message is already on the console, the message will not be displayed a second time. If the utility file system is not quiesced and the message is on the screen, the message will no longer be highlighted. If the utility file system is quiesced and unquiesced within the 30 second sleep window of the thread, then no message will be displayed. This message is intended to provide information that can be used to take action if there is a perceived slow down in DSFS response time.

System action

The program continues.

Administrator response:

Determine if the utility file system should be unquiesced.

IDFS00158E

Utility file system *utility* *name* failed to reopen.

Explanation

The utility file system failed to reopen locally, possibly due to a DASD outage, some other connectivity difficulties to the DASD, or a hardware failure. This can also happen if the utility file system is encrypted and there is an ICSF problem, DSFS will not be able to process any operations.

utility name

Name of the utility file system.

System action

The program continues.

Administrator response:

If the utility file system is encrypted and there is an ICSF problem, follow diagnostic procedures in *z/OS Cryptographic Services ICSF System Programmer's Guide*. Otherwise, unmount and remount the utility file system or restart DSFS if in a shared file system environment.

Explanation

The specified task running in DSFS has called a system service to perform an operation. The operation is, for example, opening or closing the specified data set. This operation has not returned to DSFS for at least 3 intervals of the hang detector.

asid

Asid of task.

TCB_address

TCB address of task.

action

Action phrase and object of action.

System action

The program continues.

Administrator Response

Try to correct the problem by following documented troubleshooting procedures for the specified operation. If the IDFS00159I message remains on the screen, complete the steps in [Steps for diagnosing and resolving DSFS hangs in z/OS Data Set File System Administration](#).

Table 1. Troubleshooting hits for specified operations

Action_object	See
Altering data set name	z/OS DFSMSdfp Advanced Services and z/OS DFSMS Access Method Services Commands .
Calling catalog search interface	z/OS DFSMS Managing Catalogs .
Closing dataset	<ul style="list-style-type: none"> • Using VERIFY to process improperly closed data sets in z/OS DFSMS Using Data Sets. • Recovering from errors due to an improperly closed VSAM data set in z/OS DFSMS Using Data Sets. • Checking for problems in catalogs and data sets in z/OS DFSMS Using Data Sets.
Dequeuing	z/OS MVS Planning: Global Resource Serialization .
Growing dataset	z/OS DFSMSdsm Diagnosis or z/OS DFSMSdsm Managing Your Own Data .
Locating dataset	Checking for problems in catalogs and data sets in z/OS DFSMS Using Data Sets .
Opening dataset	Opening a data set in z/OS DFSMS Using Data Sets .
Recalling dataset	z/OS DFSMSdsm Storage Administration and z/OS DFSMSdsm Managing Your Own Data .
Updating high used relative byte address (HURBA)	Requesting that DFSMSdss double-check data set high used RBA values for LDS data sets in z/OS DFSMSdss Storage Administration
Waiting for I/O	z/OS DFSMS Using Data Sets .
Allocating data set	If you are dumping the DSFS address space, also dump the ALLOCAS address space.

Table 1. Troubleshooting hits for specified operations (continued)

Action_object	See
Unallocating	If you are dumping the DSFS address space, also dump the ALLOCAS address space.
Getting member list for	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> and <i>z/OS DFSMS Access Method Services Commands</i> .
Getting statistics for	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> .
Getting RESERVE for	For more information about the RESERVE macro, see RESERVE description in <i>z/OS MVS Programming: Authorized Assembler Services Reference LLA-SDU</i> . For more information about the UCLOCK macro, see UCLOCK description in <i>z/OS MVS Programming: Authorized Assembler Services Reference SET-WTO</i> .
Releasing RESERVE for	For more information about the DEQ macro, see DEQ description in <i>z/OS MVS Programming: Authorized Assembler Services Reference ALE-DYN</i> .
Finding out if PDSE contains loadmod	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> .
Finding out if PDS contains loadmod	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> .
Reading data set	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> .
Writing data set	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> .
Checking ds authorization for	Waits troubleshooting table in <i>z/OS Security Server RACF® Diagnosis Guide</i> .
Deleting	For more information about data sets, see <i>z/OS DFSMS Using Data Sets</i> .

IDFS00160I Task **asid=asid tcb=TCB_address** appears to be delayed.

Explanation

The specified user task running in DSFS has been running for at least three intervals of the hang detector. There can be many reasons for this behavior which are expected. For example, the task has a low dispatch priority that is preventing its progress, or the task is swapped out, or the system has a resource constraint such as an auxiliary storage shortage. It could also be doing a long-running task, or looping. Another possibility is that DSFS has called another system service (not covered in message IDFS00159I) and it has not returned.

asid

Asid of task.

TCB_address

TCB address of task.

System action

The program continues.

Administrator response:

Try to determine if there is a problem by following documented troubleshooting procedures.

IDFS00161I Mounting utility file system **filesystem_name** is delayed, SMS is not active.

Explanation

The Storage Management Subsystem is not active. DSFS will wait for up to one minute for SMS to become active then the mount will fail if SMS is still not active.

filesystem_name

The name of the utility file system being mounted.

System action

The program continues.

Administrator response:

If SMS is not active, consult SMS diagnostics to determine the cause. This can be a temporary situation due to a long running SMS user exit. This situation may clear itself.

IDFS00162A

Error *error_code* initializing the DSFS kernel control program.

Explanation

The DSFS kernel control program IDFFSCM encountered an unexpected error during initialization.

error_code

The error code for the initialization failure.

System action

The program continues.

Administrator response:

Contact IBM service.

IDFS00164I

There is *number* task(s) delayed outside DSFS while *action*.

Explanation

The specified number of task(s) running in DSFS has called a system service to perform an operation. The operation is, for example, enqueue waiting for the specified data set. This operation has not returned to DSFS for at least 3 intervals of the hang detector.

number

The number of tasks.

action

Action phrase and object of action.

System action

The program continues.

Administrator response:

Try to correct the problem by following documented troubleshooting procedures for the operation specified.

IDFS00165I

DSFS is low on storage.

Explanation:

DSFS has determined that less than 40MB of storage is remaining in the address space. While in this condition, storage obtains for things associated with the creation of vnodes will be failed.

System action

The program continues.

Administrator response:

Get a storage report via F DSFS,QUERY,STORAGE,DETAILS in order to determine where unnecessary storage is being used. Take steps to limit the storage being used by that area, and perhaps even restart DSFS if

necessary to get back to a more stable environment. See other diagnostic procedures in *z/OS Data Set File System Administration*. Continue to monitor the situation, and if uncontrollable or unacceptable, then get dumps with both OMVS and DSFS address spaces and call IBM Service.

IDFS00166I **DSFS is critically low on storage.****Explanation:**

DSFS has determined that less than 20MB of storage is remaining in the address space. While in this condition, all DSFS storage obtains will be failed.

System action

The program continues.

Administrator response:

Get a storage report via F DSFS,QUERY,STORAGE,DETAILS in order to determine where unnecessary storage is being used. Take steps to limit the storage being used by that area, and perhaps even restart DSFS if necessary to get back to a more stable environment. See other diagnostic procedures in *z/OS Data Set File System Administration*. Continue to monitor the situation, and if uncontrollable or unacceptable, then get dumps with both OMVS and DSFS address spaces and call IBM Service.

IDFS00167E **Space monitoring initialization for *name* has failed.****Explanation**

DSFS either had an internal error or a lack of storage which was detected when attempting to initialize the necessary environment for space monitoring.

name

The utility file system name.

System action

The program continues.

Administrator response

None.

IDFS00168I **DSFS suppressing a dump for an error condition.****Explanation:**

DSFS has encountered an error condition that would normally cause a system dump to be taken. However, DSFS has determined that it is already taking a dump on another task. Therefore, the dump for this error is being suppressed.

System action

The program continues.

Administrator response:

Ensure that a DSFS dump is produced automatically. If one is not, then follow troubleshooting procedures.

IDFS00169I **Starting FSINFO command.****Explanation:**

The FSINFO command is now processing. There will be an IDFS00260I message indicating that the display from this modify command is completed.

System action

The program continues.

Administrator response

None.

IDFS00171E	Utility file system <i>utility_name</i> has reached the maximum architected size.
-------------------	--

Explanation

The specified utility file system has reached the maximum architected size and can no longer be grown. The maximum architected size is approximately 16 TB.

utility_name

The name of the utility file name.

System action

The program continues.

Administrator response:

The maximum size has been reached. There is no action that can be taken to get any more space in the utility file system.

IDFS00172E	Utility file system <i>utility_filename</i> is disabled for writing.
-------------------	---

Explanation

The specified utility file system is disabled for writing. Utility file systems in this state cannot be salvaged until DSFS is restarted.

utility_filename

The name of the utility file name.

System action

Salvage operation terminates and a DSFS restarted is attempted. When the utility file system is remounted, a salvage will be attempted. The utility file system may be still usable, or else it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and that the utility file system is remounted.

IDFS00173E	Could not read 8K page <i>block_number</i> from utility file system <i>utility_filename</i>.
-------------------	---

Explanation

An error occurred that prevented the online salvage program from reading the specified block number. This means that the utility file system is damaged. DSFS will be restarted, and when the utility file system is remounted, it may be salvaged again, and it may be reformatted.

block_number

The block number.

utility_filename

The name of the utility file name.

System action

Salvage operation terminates DSFS, and a restart is attempted.

Administrator response:

If the problem is due to I/O error, DSFS will issue additional messages, the administrator will need to correct the I/O errors with the device before proceeding.

IDFS00174E	Errors encountered verifying AFL on utility file system <i>utility_filename</i>.
-------------------	---

Explanation

An error occurred verifying the AFL (file system list for the utility file system) on the utility file system. This means that the utility file system is damaged. This message is intended for IBM service personnel and is preceded by messages that indicate what errors occurred while verifying the AFL.

utility_filename

The name of the utility file name.

System action

Salvage operation terminates DSFS, and a restart is attempted. When the utility file system is remounted, it will be reformatted.

System action:

Ensure DSFS is restarted and utility file system remounted.

IDFS00175E**Corruption: *corruption_text*.**

Explanation

A corruption was found on the utility file system. The provided text is intended for IBM service. Additional messages will indicate the action taken by the salvage program, for example, whether the salvage program will continue or not based on the severity of the error.

corruption_text

Text information describing the corruption.

System action

Salvage operation terminates DSFS, and a restart is attempted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and the utility file system is remounted.

IDFS00176E**Expected: *expected_value***

Explanation

A corruption was found on the utility file system. This message was preceded by a message showing the corrupted values in a region of the utility file system. This message shows the expected values in the specified region of the utility file system. This message is intended for IBM service. Additional messages will follow which will indicate the action taken by the salvage utility.

corruption_value

Text information describing the expected value.

System action

Salvage operation continues.

Administrator response:

Ensure that DSFS is restarted and the utility file system is remounted.

IDFS00177I**Formatted *vversion_number* utility file system size *formatted_size* 8K blocks, data set size *VSAM_size* 8K blocks.**

Explanation

This message displays the utility file system version, formatted size, in 8 K blocks, of the utility file system (the amount that the DSFS format utility has formatted) and the current initialized (used) size of the data set that contains the DSFS utility file system.

version_number

The utility file system version number.

formatted_size

The formatted size.

VSAM_size

The size of the VSAM data set.

System action

Salvage operation continues.

Administrator response:

Examine subsequent messages provided by the salvage utility to determine if action is required.

IDFS00179I**Log file size *logfile_size* 8K blocks, verified correct.****Explanation**

The logfile was found to be correct during a utility file system salvage operation.

logfile_size

The size of the log file in 8K blocks.

System action

The system continues.

Administrator response

None.

IDFS00180E**Log file on utility file system *utility_filename* is corrupted.****Explanation**

The log file on the utility file system has severe corruption, the salvage operation cannot be completed and the utility file system is marked damaged.

utility_filename

The name of the utility file system.

System action:

Salvage operation ends and DSFS is restarted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and the utility file system is remounted.

IDFS00181I**Bitmap size *bitmap_size* 8K blocks, verified correct.****Explanation**

The bitmap was found to be correct during a utility file system salvage operation.

bitmap_size

The size of the bitmap in 8K blocks.

System action

The program continues.

Administrator response

None.

IDFS00182E**Bitmap on utility file system *utility_filename* is corrupted.**

Explanation

The block allocation bitmap on the utility file system has severe corruption, the salvage operation cannot be completed and the utility file system is marked damaged. This message is intended for IBM service personnel and is preceded by messages that indicate what errors occurred while verifying the bitmap structure.

utility_filename

Name of the utility file system.

System action

Salvage operation ends and DSFS is restarted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and the utility file system is remounted.

IDFS00183I**Utility file system was successfully verified.**

Explanation:

A utility file system was successfully verified by the **dsadm salvage** command.

System action

The program ends.

Administrator response

None.

IDFS00184E**Could not salvage utility file system because it could not be found.**

Explanation:

The utility file system either does not exist, cannot be accessed or is not a DSFS utility file system.

System action

The program ends.

Administrator response:

Check the DSFS utility file system and try the operation again.

IDFS00185E**Error *error_code* reason code *reason_code* received salvaging the utility file system.**

Explanation

A utility file system could not be salvaged due to an unexpected error, or possibly the utility file system was busy with another command or operation.

error_code

The error code received

reason_code

The reason code received

System action

Salvage operation ends.

Administrator response:

If there are no other commands or operations running against the utility file system, and the problem continues, contact your service representative.

IDFS00188I**DSFS is low on recovery tasks.****Explanation:**

DSFS has determined that 80%, or more, of the recovery tasks in the address space are actively performing recovery actions.

System action

The program continues.

Administrator response:

A large number of DSFS operations have been canceled, causing recovery actions to take place. Either these actions are not being done in a timely manner, or there is a system problem that will soon drastically affect the ability of DSFS to properly perform its operations. You should begin looking for the cause of all these cancel actions.

IDFS00189I**DSFS is critically low on recovery tasks.****Explanation:**

DSFS has determined that 95%, or more, of the recovery tasks in the address space are actively performing recovery actions.

System action

The program continues.

Administrator response:

A large number of DSFS operations have been canceled, causing recovery actions to take place. Either these actions are not being done in a timely manner, or there is a system problem that will soon drastically affect the ability of DSFS to properly perform its operations. You should begin looking for the cause of all these cancel actions.

IDFS00190I**Primary file system size *filesystem_size* 8K blocks, verified correct.****Explanation**

The primary file system was found to be correct during a utility file system salvage operation.

filesystem_size

The size of the primary file system in 8K blocks.

System action

The program continues.

Administrator response

None.

IDFS00191E**Primary file system on utility file system *utility_filename* is corrupted.****Explanation**

The primary file system is corrupted. There may be other messages describing the corruption. DSFS will attempt a restart to remount the utility file system and reformat it.

utility_filename

The name of the utility file system.

System action

Salvage operation ends and DSFS is restarted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and the utility file system is remounted.

IDFS00197I	Verification of utility file system <i>utility_filename</i> started.
-------------------	---

Explanation

Indicates that salvage started verifying a utility file system with displayed utility file system name.

utility_filename

The name of the utility file system.

System action

The program continues.

Administrator response

None.

IDFS00198I	Verification of utility file system <i>utility_filename</i> completed, no errors found.
-------------------	--

Explanation

Indicates that salvage completed verifying the specified utility file system name and there is no error found with the utility file system during the salvage run.

utility_filename

The name of the utility file system.

System action

The program ends.

Administrator response

None.

IDFS00200I	Verification of utility file system <i>utility_filename</i> completed and the utility file system is in error.
-------------------	---

Explanation

Indicates that salvage completed verifying the specified utility file system name. Some errors were found with the utility file system during the salvage run.

utility_filename

The name of the utility file system.

System action

Salvage operation ends and DSFS is restarted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and utility file system remounted.

IDFS00201I	Verification of utility file system <i>utility_filename</i> stopped with return code <i>return_code</i> due to major error(s).
-------------------	---

Explanation

Salvager encountered one of the following errors during verification and could not continue on. The return code is *return_code*.

EIO(122) - Salvager could not read or write the DASD.
ENOMEM(132) - Salvager ran out of storage.
EMVSERR(157) - Salvager had an internal error.

utility_filename

The name of the utility file system.

return_code

The return code.

System action

Salvage operation ends and DSFS is restarted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and utility file system remounted.

IDFS00202I	Salvage found <i>number_errors</i> minor errors in utility file system <i>utility_filename</i>.
-------------------	--

Explanation

Errors were found during the salvage run. The utility file system name is displayed in the message.

number_errors

The name of the utility file system.

utility_filename

The name of the utility file system.

System action

The program ends.

Administrator response

None.

IDFS00203I	DSFS kernel initiated at <i>time_created</i> Current status: <i>current_status</i>.
-------------------	--

Explanation

This message is a response to the QUERY,STATUS modify command. It shows the time the DSFS address space was started and its current operational status.

time_created

The time when the DSFS address space was created.

current_status

The current status of DSFS (initializing, shutting down, aborting, active).

System action

The program continues.

Administrator response

None.

IDFS00204I	Salvage processed <i>directory_pages</i> directory pages, <i>number_anodes</i> anodes, <i>number_ibs</i> indirect blocks and <i>anode_pages</i> anode table pages.
-------------------	---

Explanation

During the salvage run, there are displayed numbers of directory pages, anodes, indirect blocks and anode table pages being processed.

directory_pages

The number of directory pages.

number_anodes

The number of anodes.

number_ibs

The number of indirect blocks.

anode_pages

The number of anode table pages.

System action

The program continues.

Administrator response

None.

IDFS00206E	Time limit exceeded for recovery of in-progress operations for filesystem <i>filesystem_name</i>.
-------------------	--

Explanation

DSFS has taken a terminating exception, and the DSFS kernel program IDFFSKN has waited 5 minutes for in-progress user file operations to recover before proceeding with IDFFSKN termination. Since recovery was not performed within the 5 minute window then IDFFSKN termination will proceed and DSFS will stop and be restarted by z/OS UNIX.

filesystem_name

The name of the file system.

System action

The program continues.

Administrator response

None.

IDFS00212E	Verification of utility file system terminated because error limit <i>max_errors</i> exceeded.
-------------------	---

Explanation

Indicates salvage encountered too many errors.

max_errors

The error limit.

System action

Salvage operation ends and DSFS is restarted. When the utility file system is remounted, it will be reformatted.

Administrator response:

Ensure that DSFS is restarted and the utility file system remounted.

IDFS00222A	Restarting exception <i>abend_code</i> occurred, reason <i>reason_code</i> abend psw <<i>high_first</i> <i>low_first</i>>< <i>high_second</i> <i>low_second</i>>
-------------------	---

Explanation

A DSFS program encountered an exception running in AMODE64. A dump will be issued. DSFS will be automatically stopped and restarted. Files that are currently mounted may see IO errors. During the DSFS restart, the system may display a BPXF032D message that must be replied to for DSFS to reinitialize.

abend_code

The z/OS abend code received.

reason_code

The z/OS reason code received.

high_first

The high half of the first doubleword of the abend PSW.

low_first

The high low of the first doubleword of the abend PSW.

high_second

The high half of the second doubleword of the abend PSW.

low_second

The low half of the second doubleword of the abend PSW.

System action

The program continues.

Administrator response:

This message will be followed by additional messages indicating more about the problem. Contact your service representative.

IDFS00223I

General Registers *register_number*: <*high_first low_first* ><*high_second low_second*>< *high_third low_third*>< *high_fourth low_fourth*>

Explanation

A DSFS program running in AMODE64 encountered an exception. This message shows the 64-bit registers at time of error.

register_number

The register number.

high_first

The high half of a 64-bit register.

low_first

The high half of a 64-bit register.

high_second

The high half of a 64-bit register.

low_second

The low half of a 64-bit register.

high_third

The high half of a 64-bit register.

low_third

The low half of a 64-bit register.

high_fourth

The high half of a 64-bit register.

low_fourth

The low half of a 64-bit register.

System action

The program continues.

Administrator response:

This message will be followed by additional messages indicating more about the problem. Contact your service representative.

IDFS00224A

DSFS kernel out of storage above bar, total of <high_megabytes,, low_megabytes> bytes used, size attempted was <high_storage,, low_storage>, class class_number type storage_type.

Explanation

The DSFS kernel ran out of storage above the 2G bar when attempting to obtain *high_storage,,low_storage*. *high_megabytes,, low_megabytes* is the number of bytes that has been obtained and assigned by the DSFS kernel above the bar already. *class_number* and *storage_type* is information for IBM service personnel.

high_megabytes

The high half of the total number of megabytes used by DSFS.

low_megabytes

The low half of the total number of megabytes used by DSFS.

high_storage

The high half of amount of storage that DSFS attempted to obtain.

low_storage

The low half of amount of storage that DSFS attempted to obtain.

class_number

The class number of the DSFS kernel subcomponent.

storage_type

The storage type of the DSFS kernel.

System action

The program ends.

Administrator response:

Try restarting DSFS with smaller cache sizes. This message is followed by output showing the DSFS kernel storage map. If problem continues, contact your service representative.

IDFS00227I

Salvage has verified *objects_processed* of *number_objects* *object_description* in the *filesystem_description*.

Explanation

During the salvage run, this indicates approximate progress on how many items in the described file system object have been verified.

objects_processed

The number of objects that were processed.

number_objects

The number of objects in the file system structure.

object_description

The description of the object.

filesystem_description

The description of the file system structure being verified.

System action

The program continues.

Administrator response

None.

IDFS00228E**Utility file system *utility_filename* is damaged.****Explanation**

During the salvage run, the utility file system was found to be damaged.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

Mount will reformat the corrupted utility file system.

IDFS00229E**Non-terminating exception *abend_code* occurred, reason *reason_code*
abend psw <*high_first low_first*> <*high_second low_second*>****Explanation**

A DSFS kernel subroutine encountered an exception running AMODE64. A dump will be issued. This exception is non-terminating, the DSFS kernel will continue to run, though there may be errors encountered for a given file or utility file system.

abend_code

The z/OS abend code received.

reason_code

The z/OS reason code received.

high_first

The high half of the first doubleword of the abend PSW.

low_first

The low half of the first doubleword of the abend PSW.

high_second

The high half of the second doubleword of the abend PSW.

low_second

The low half of the second doubleword of the abend PSW.

System action

The program continues.

Administrator response:

This message will be followed by additional messages indicating more about the problem. Contact your service representative.

IDFS00231I**Utility file system *utility_filename* was not unmounted cleanly. Last
update time stamp=*time_stamp* sysname=*system_name*.****Explanation**

At the beginning of the salvager run, the utility file system was found to have not been unmounted cleanly after last use. The time stamp indicates the last periodic update time. The system name is where the last update occurred.

utility_filename

The utility file system name.

time_stamp

The time stamp.

system_name
The system name.

System action

The program continues.

Administrator response

None.

IDFS00233E	Failed to prepend the current working directory, error=<i>error_code</i> reason=<i>reason_code</i>.
-------------------	--

Explanation
Either BPX1GCW failed to return the current working directory or the length of the full directory names exceeds 1024.

error_code
The error code.

reason_code
The reason code.

System action

The program ends.

Administrator response

None.

IDFS00234E	Failed to get information for directory <i>directory_name</i>, error=<i>error_code</i> reason=<i>reason_code</i>.
-------------------	--

Explanation
Failed to get information for the specified object.

directory_name
The directory name.

error_code
The error code.

reason_code
The reason code.

System action

The program ends.

Administrator response:
Correct the error and retry the command.

IDFS00235I	Skip page <i>logical page</i> (physical page <i>physical_page</i>) of directory (index=<i>index_number</i>).
-------------------	---

Explanation
The indicated directory page was too corrupted to continue and salvager will skip processing the rest of entries and move on to the next directory page.

logical_page

The logical page number of the directory page.

physical_page

The physical page number of the directory page.

index_number

The index number of the directory.

System action

The program continues.

Administrator response

None.

IDFS00236I

Found more than *max_entries* entries in directory (index=*index_number*) and skipping duplicate name checking for any additional entries.

Explanation

Salvager has found more than specified number of valid entries in a directory indicated by the index number. To avoid any potential storage shortage, salvager will suspend duplicate name checking for any additional entries found in the same directory.

max_entries

The maximum number of entries allowed in duplicate name checking

index_number

The index number of the directory.

System action

The program continues.

Administrator response

None.

IDFS00238E

Failed to get file system information for utility file system, error=*error_code* reason=*reason_code*.

Explanation

An error occurred while trying to get information for the specified utility file system. See Return codes (errno) in *z/OS UNIX System Services Messages and Codes* for a description of the error code. See *Appendix A, Reason codes*, for a description of the reason code.

error_code

The error code.

reason_code

The reason code.

System action

The program ends.

Administrator response:

Correct the error and try again.

IDFS00239I

In a wait to verify that utility file system *utility_filename* has no other writers. Member *member_namesysplex_name* last wrote to the utility file system on *time*.

Explanation

When a utility file system is cleanly unmounted, DSFS can quickly determine that there are no other members writing to the utility file system. This utility file system was not cleanly unmounted and DSFS needs to wait 65 seconds to verify that there are no other members writing to the utility file system.

utility_filename

Name of the utility file system.

member_name

The member name.

sysplex_name

The sysplex name or is not passed.

time

The time of the last recorded block zero write of the utility file system.

System action

The program continues.

Administrator response

None.

IDFS00240E

Dynamic allocation error occurred for data set *dataset_name*. *rc=return_code err=return_error info=return_info SMSreason=return_reason func=function_code*.

Explanation

A dynamic allocation error occurred while processing the specified data set. *return_code*, *return_error*, *return_info* and *return_reason* are the error codes supplied by dynamic allocation. *Function_code* describes the dynamic allocation function attempted. Retcode=450 indicates concurrent allocations exceeded the system limit. If no extended TIOT is requested, the limit is determined by the TIOT size. TIOT size is specified in the ALLOCxx member of PARMLIB, or by system default. If extended TIOT is requested, there is no limit (extended TIOT is specified in the DEVSUPxx member of PARMLIB via NON_VSAM_XTIOT=YES option).

dataset_name

The data set name.

return_code

The return code.

return_error

The return error.

return_info

The return information.

return_reason

The return reason.

function_code

The function code.

System action

The program continues.

Administrator response:

Use the dynamic error codes to determine the reason for the failure. Correct the error and retry the operation.

IDFS00242E	<i>program_name</i>: MODIFY command - <i>command_name</i> rejected: rc = EBUSY.
-------------------	--

Explanation

The same MODIFY command is being processed or all DSFS modify command threads are busy processing a long running MODIFY command, or DSFS is being shut down.

program_name

The program name.

command_name

The command name.

System action

The program continues.

Administrator response:

If DSFS is shutting down, then reissue the command after it is restarted. Otherwise, reissue the command after one of the other MODIFY commands is completed.

IDFS00243E	<i>program_name</i>: MODIFY command - <i>command_name</i> failed: rc = <i>return_code</i>.
-------------------	---

Explanation

An error occurred while attempting a console command.

program_name

The program name.

command_name

The command name.

return_code

The return code.

System action

The program continues.

Administrator response:

Check the meaning of the return code and respond accordingly.

IDFS00244E	Utility file system <i>filesystem_name</i> has been quiesced for at least <i>min_seconds</i> seconds by operation <i>operation</i>. It was quiesced by <i>quiesce_cause</i> at <i>quiesce_time</i> (GMT).
-------------------	--

Explanation

The utility file system is quiesced and there is at least one task waiting to access it. Access will be allowed when the utility file system is unquiesced.

filesystem_name

The utility file system name.

min_seconds

The minimum number of seconds a utility file system must be quiesced before it can appear in this message.

operation

The name of the operation causing the quiesce.

quiesce_cause

Either the asid and job causing the quiesce or an indication that DSFS is causing the quiesce.

quiesce_time

Time of the quiesce.

System action

The program continues.

Administrator response:

If the condition persists, contact your service representative.

IDFS00248I

program_name: MODIFY command - *command* accepted.

Explanation

The MODIFY command *command* has been accepted.

program_name

The program name.

command

The command name.

System action

The program continues.

Administrator response

None.

IDFS00255E

Failed to get file system information error=*error_code*
reason=*reason_code*.

Explanation

Getting file system information has failed due to the displayed return code and reason code.

error_code

The error code.

reason_code

The reason code.

System action

The program continues.

Administrator response:

Correct the error and retry.

IDFS00256E

Invalid option *option*.

Explanation

Bad option is specified for FSINFO command.

option

The bad option.

System action

The program continues.

Administrator response:

Correct the error and retry.

IDFS00260I **FSINFO command done.**

Explanation:

The FSINFO command completed processing.

System action

The program continues.

Administrator response

None.

IDFS00261I **File System Status:**

Explanation:

Indicates that the information following the message is the status of the DSFS utility file system and the statistics for it are displayed. There will be an IDFS00260I message indicating that the display from this MODIFY command is completed.

System action

The program continues.

Administrator response

None.

IDFS00262I **Processing zlc for *filesystem_name*.**

Explanation

The specified utility file system is being mounted. There are files in it which were marked as deleted while the utility file system was last being used. Those files had not yet been removed from disk. These files are now being removed from disk. This is normal zero link count (zlc) processing.

filesystem_name

The utility file system being attached.

System action

The program continues.

Administrator response

None.

IDFS00263I **There are no free 8K blocks remaining in utility file system *utility_filename*. Applications may fail.**

Explanation

Applications may be failing because there are no free 8K blocks in the utility file system. The utility file system must be grown or applications may continue to fail.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

Determine why the utility file system does not dynamically grow. If in a shared file system environment, restart DSFS to get the utility file system to automatically remount. Otherwise, unmount and remount the utility file system.

IDFS00264I**Salvage for utility file system was successfully canceled.**

Explanation:

An online salvage for the utility file system was successfully canceled.

System action

Salvage operation ends.

Administrator response

None.

IDFS00269I**Salvage for utility file system *utility_filename* has been interrupted.**

Explanation

The salvage for utility file system has been interrupted by a **dsadm salvage -cancel** command or by an unmount.

utility_filename

The utility file system name.

.

System action

The program continues.

Administrator response

None.

IDFS00271E**The request cannot be satisfied because the DSFS kernel is not active.**

Explanation:

The **dsadm** command fails because the DSFS kernel is not active.

System action

The program ends.

Administrator response:

Activate the DSFS kernel and try the command again.

IDFS00272E**The request cannot be satisfied because the IDFFSPRM value for *parameter_name* could not be retrieved from the DSFS kernel.**

Explanation

The value for the specified IDFFSPRM parameter could not be retrieved.

parameter_name

The IDFFSPRM name.

System action

The program ends.

Administrator response:

Determine why the value cannot be retrieved and try the command again.

IDFS00273E *program_name: could not open trace output file trace_filename.*

Explanation

The in-memory trace table could not be printed because the output UNIX trace file could not be opened.

program_name

Name of the DSFS program.

trace_filename

The trace file name.

System action

The program continues.

Administrator response:

Retry the **dsadm** command with a valid UNIX trace file name that can be opened for output.

IDFS00274E *Message id message_ID not found.*

Explanation

DSFS attempted to issue a message and the message could not be found.

message_ID

The ID of the message that DSFS attempted to issue.

System action

The program continues.

Administrator response:

Contact your service representative.

IDFS00279A *Terminating exception abend_code occurred, reason return_code abend
psw first_word second_word*

Explanation

A DSFS kernel sub-routine encountered an exception. A dump will be issued. Severe problems encountered during initialization will result in the termination of DSFS and the system will display a BPXF032D message that must be replied to for DSFS to reinitialize.

abend_code

The z/OS abend code received.

return_code

The z/OS reason code received.

first_word

First word of the abend PSW.

second_word

Second word of the abend PSW.

System action

The program continues.

Administrator response:

This message may be preceded by messages indicating more about the problem. This message will be followed by additional messages indicating more about the problem. Contact your service representative.

IDFS00280A	Terminating exception <i>abend_code</i> occurred, reason <i>reason_code</i> abend psw <<i>first_high first_low</i>> <<i>second_high second_low</i>>
-------------------	--

Explanation

A DSFS kernel sub-routine encountered an exception running in AMODE64. A dump will be issued. Severe problems encountered during initialization will result in the termination of DSFS and the system will display a BPXF032D message that must be replied to for DSFS to reinitialize.

abend_code

The z/OS abend code received.

reason_code

The z/OS reason code received.

first_high

High half of the first doubleword of the abend PSW.

first_low

Low half of the first doubleword of the abend PSW.

second_high

High half of the second doubleword of the abend PSW.

second_low

Low half of the second doubleword of the abend PSW.

System action

The program continues.

Administrator response:

This message may be preceded by messages indicating more about the problem. This message will be followed by additional messages indicating more about the problem. Contact your service representative.

IDFS00281E	<i>program_name</i>: MODIFY command - <i>command_name</i> has been rejected.
-------------------	---

Explanation

The MODIFY command *command_name* has been rejected.

program_name

The program name.

command_name

The command name.

System action

The program continues.

Administrator response:

The *command_name* command cannot be processed until the DSFS kernel has completed initialization. Retry the command after initialization completes. If initialization does not complete, DSFS may need to be canceled. An ABORT can also result in this error. If the problem continues, contact your service representative.

IDFS00282I	Utility file system <i>utility_filesystem</i> anode table length=<i>anode_size</i> (in 8K blocks) LPI=<i>LPI_value</i> encrypt_<i>status</i> compression_<i>status</i>.
-------------------	--

Explanation

Displays the encryption and compression attributes of the utility file system before verifying anode table pages. The information is intended for IBM service personnel.

utility_filesystem

Name of the utility file system.

anode_size

The anode table size in 8K.

LPI_value

The LPI value.

encrypt_status

The encryption status.

compression_status

The compression status.

System action

The program continues.

Administrator response

None.

IDFS00283E

DSFS failed to assign key label *key_label* to *utility_filesystem* because it is not known to ICSF.

Explanation

ICSF does not recognize the key label.

key_label

The key label.

utility_filesystem

Name of the utility file system.

System action

The program continues.

Administrator response:

Ensure that the correct key label is specified and try the command again.

IDFS00284E

ICSF could not be contacted to verify key label *key_label* for utility file system *utility_filesystem*.

Explanation

The key label must be known to ICSF before it can be used when defining or encrypting a DSFS utility file system.

key_label

The key label.

utility_filesystem

Name of the utility file system.

System action

The program continues.

Administrator response:

Ensure ICSF is running and verify that the key label is defined.

IDFS00285E

ICSF returned error code *error_code* reason code *reason_code* while verifying key label *key_label* for utility file system *utility_filename*.

Explanation

A problem was encountered using ICSF to verify a key label.

error_code

The error code.

reason_code

The reason code.

key_label

The key label.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

Correct the problem and try the command again. Reason codes are documented in *z/OS Cryptographic Services ICSF Application Programmer's Guide*.

IDFS00286E**IDFFSKN termination hang, detaching IDFFSKN.**

Explanation:

IDFFSKN has started the termination process for a shutdown command or a DSFS severe software error (abort). However, program IDFFSCM has detected a delay in that processing and considers that process is hung and is taking action to force termination to continue by detaching the IDFFSKN program. A detach abend might occur but termination now proceeds. The DSFS restart prompt will likely be issued.

System action

The program continues.

Administrator response:

Contact your service representative.

IDFS00287E**IO driver termination problem detected, continuing termination.**

Explanation:

IDFFSKN main task has detected that there were problems encountered while terminating the DSFS IO driver during a shutdown operation or an abnormal termination. Termination processing continues but DSFS will end and the DSFS restart prompt will likely be issued.

System action

The program continues.

Administrator response:

Contact your service representative.

IDFS00288E**Memory registration service FPZ4RMR failed with return code
return_code reason code reason_code.**

Explanation

DSFS will attempt to fix the file cache via the zEDC FPZ4RMR function if DSFS compression is requested via mounting a compressed file system or specifying EDCFIXED for the file cache. This message is shown for each file cache space that could not be fixed. DSFS will attempt to fix as many file cache spaces as it can in this case. The QUERY,FILECACHE command can be used to determine which cache spaces are fixed via FPZ4RMR service.

return_code

The return code.

reason_code

The reason code.

System action

The program continues.

Administrator response:

The system determines if DSFS can fix a cache space, it is determined by the amount of DMA memory available on the system and the usage of that memory by other applications on the system. Thus this might be a normal response for your system. The message is provided to alert the administrator in case they want to examine DMA memory usage.

IDFS00289E

The encryption type associated with key label *key_label* is not supported by DFSMS.

Explanation

DFSMS only supports AES-256 XT protected key encryption.

key_label

The key label.

System action

The program continues.

Administrator response:

Try a different key label.

IDFS00290E

***component_name* returned error code *error_code* reason code *reason_code* while trying to open utility file system *utility_filename*.**

Explanation

A problem was encountered while opening a utility file system.

component_name

The component.

error_code

The error code.

reason_code

The reason code.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

See accompanying message IEC161I, correct the problem, and try the command again.

IDFS00292E

Dynamic allocation abend occurred for data set *dataset_name*. Abend code=*abend_code* func=*function_code*.

Explanation

Dynamic allocation abended while processing the specified data set. The abend code returned by the system is as shown. *Function_code* describes the dynamic allocation function that was attempted.

dataset_name

The data set name.

abend_code

The abend code.

function_code

The function code.

System action

The program continues.

Administrator response:

Review the system logs for error messages related to dynamic allocation and the specified data set. Correct the error and retry the operation.

IDFS00293I**Waiting for *service_name* to initialize.****Explanation**

The named service is not available. DSFS is waiting to allow the service to initialize.

service_name

The service name.

System action

The program continues.

Administrator response

None.

IDFS00294I**Wait ending and *service_name* is not initialized.****Explanation**

After waiting, the named service is still not initialized. Operations requiring this service will fail.

service_name

The service name.

System action

The program continues.

Administrator response:

Determine why the named service will not initialize and restart the service.

IDFS00295I***service_name* is now initialized.****Explanation**

The named service is now available.

service_name

The service name.

System action

The program continues.

Administrator response:

Operations that failed because the service was not initialized can now be retried.

IDFS00296I**The wait for *service_name* initialization ended because DSFS is being stopped or restarted.**

Explanation

DSFS has stopped waiting for the named service to initialize.

service_name

The service name.

System action

The program continues.

Administrator response:

When DSFS restarts, ensure the named service is initialized before retrying operations that require the service.

IDFS00297I

The wait for *service_name* initialization is not started because DSFS is being stopped or restarted.

Explanation

Since DSFS is being stopped or restarted, it does not need to wait for the initialization of the named service.

service_name

The service name.

System action

The program continues.

Administrator response:

When DSFS restarts, ensure the named service is initialized before retrying operations that require the service.

IDFS00298E

Mount for utility file system *utility_filename* failed because ICSF is not initialized.

Explanation

ICSF is not initialized. DSFS cannot mount a utility file system that has a key label if ICSF is not initialized.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

Try the operation again after ICSF is initialized.

IDFS00299E

Mount for utility file system *utility_filename* failed because DSFS is being stopped or restarted.

Explanation

Mounts that are waiting for ICSF to initialize are failed when DSFS is being stopped or restarted.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

Try the mount again when ICSF is initialized and DSFS is not being stopped or restarted.

IDFS00300E	Open for utility file system <i>utility_filename</i> failed because ICSF is not initialized.
<p>Explanation ICSF is not initialized. DSFS cannot open a utility file system that has a key label if ICSF is not initialized.</p> <p><i>utility_filename</i> The utility file system name.</p> <p>System action The program continues.</p> <p>Administrator response: Try the operation again after ICSF is initialized.</p>	
IDFS00301E	Open for utility file system <i>utility_filename</i> failed because DSFS is being stopped or restarted.
<p>Explanation Opens that are waiting for a ICSF to initialize are failed when DSFS is being stopped or restarted.</p> <p><i>utility_filename</i> The utility file system name.</p> <p>System action The program continues.</p> <p>Administrator response: Try the operation again when DSFS is not being stopped or restarted.</p>	
IDFS00302I	The EDCFIXED option of the filecache_size IDFFSPRM configuration option is ignored.
<p>Explanation: Since zEDC is not initialized, the EDCFIXED option cannot be processed. The file cache pages are not fixed for zEDC performance.</p> <p>System action The program continues.</p> <p>Administrator response: Once zEDC is initialized, issue the dsadm config -filecache_size command with the EDCFIXED option.</p>	
IDFS00303E	Mount for utility file system <i>utility_filename</i> failed because zEDC is not initialized.
<p>Explanation zEDC is not initialized. DSFS cannot mount a utility file system that is compressed if zEDC is not initialized.</p> <p><i>utility_filename</i> The utility file system name.</p> <p>System action The program continues.</p> <p>Administrator response: Try the operation again after zEDC is initialized.</p>	

IDFS00305I**DSFS is waiting for SMS initialization.****Explanation:**

DSFS is waiting for SMS to initialize because the IDFFSPRM configuration option `filecache_size` has the `EDCFIXED` keyword specified. DSFS will continue initialization once it receives notification that SMS is available. SMS and zEDC are required products for DSFS compression.

System action

The program continues.

Administrator response:

No action required if you plan to use compressed file systems. If DSFS is still waiting when SMS is initialized then contact the service representative. If you do not plan on using compression then remove the configuration parameter before the next IPL of the system.

IDFS00306I**DSFS is waiting for zEDC initialization.****Explanation:**

DSFS is waiting for zEDC to initialize because the IDFFSPRM configuration option `filecache_size` has the `EDCFIXED` option specified. DSFS will continue initialization once it receives notification that zEDC is available. SMS and zEDC are required products for DSFS compression.

System action

The program continues.

Administrator response:

No action required if you plan to use compressed file systems. If DSFS is still waiting when zEDC is initialized then contact the service representative. If you do not plan on using compression then remove the configuration parameter before the next IPL of the system.

IDFS00307I**Utility file system *filesystem_name* received a compression failure due to lack of zEDC devices.****Explanation**

A compression file write for one or more files in the indicated utility file system failed due to lack of zEDC devices. The file data will be stored in non-compressed format. No application errors will occur.

filesystem_name

The utility file system name.

System action

The program continues.

Administrator response

None.

IDFS00308E**Utility file system *filesystem_name* CI=*control_interval* (*data_type* inode=*inode_number*) is not stored in encrypted format.****Explanation**

A decryption read request of an extended format data set found that DSFS has stored data that is supposed to be encrypted in the clear. The type of data that is affected is in parentheses and is one of the following values: meta (internal file system metadata), compressed file, or uncompressed file. A dump is generated to provide diagnostics for IBM service. If the data is file data, then the inode of the owning file is shown. For metadata, this value is zero.

filesystem_name

The utility file system name.

control_interval

The control interval number.

data_type

The type of data affected.

inode_number

The inode number of the file affected, will be 0 for type meta.

System action

The program continues.

Administrator response:

If the data type is meta or compressed file data, then use the **dsadm salvage** command to detect the condition. This will cause the utility file system to be marked damaged and DSFS to restart. When the utility file system is remounted, it will be reformatted. If the data is uncompressed file data, then inode identifies the file and that file can be rewritten with new contents, for example, using the **cp** command to copy the file to a new name and then delete the old file and use the **mv** command to change the new file to the original name. As an alternative, you can also define a new utility file system. Report the problem to the service representative.

IDFS00313I

**Call to catalog service for data set *utility_filename* failed,
rc=return_code rsn=reason_code.**

Explanation

A call to the MVS catalog service for the specified data set failed. The return and reason codes are from the MVS catalog service. Other system processing that depends on the catalog entry may not function properly.

utility_filename

The name of the utility file system.

return_code

The catalog service return code.

reason_code

The catalog service reason code.

System action

The program continues.

Administrator response:

Catalog return and reason codes are listed in message IDC3009I in *z/OS MVS System Messages, Vol 6 (GOS-IEA)*. Find the specified return and reason codes in order to determine the problem.

IDFS00319I

Using default message table which is in English.

Explanation:

An error occurred opening or reading the messages data set pointed to by *msg_input_dsn* in the configuration data set. Verify that the message data set name is valid, exists, and is not damaged.

System action

The program continues.

Administrator response:

Check the *msg_input_dsn* variable in the configuration data set and verify that the messages data set is valid.

IDFS00320I

**Formatting to *interval_size* control interval *number_intervals* for
primary extent of *utility_filename*.**

Explanation

The DSFS device driver encountered an unformatted utility file system and is loading it.

interval_size

The control interval size.

number_intervals

The number of control intervals

utility_filename

Name of the utility file system.

System action

The program continues.

Administrator response:

None.

IDFS00324E	Could not add the specified high-level qualifier directory names to the HLQ list, error code <i>return_code</i> reason code <i>reason_code</i>.
-------------------	--

Explanation

The DSFS kernel failed to add the specified high-level qualifier directory names to the HLQ list. The specified high-level qualifier directory names can be either empty or contain an invalid name.

return_code

The return code from the DSFS kernel.

reason_code

The reason code.

System action

The program ends.

Administrator response:

Ensure the high-level qualifier directory names are valid. Use commas to separate multiple names and do not embed blanks between the names. Fix the error and try again.

IDFS00325E	Could not remove the specified high-level qualifier directory names from the HLQ list, error code <i>return_code</i> reason code <i>reason_code</i>.
-------------------	---

Explanation

The DSFS kernel failed to remove the specified high-level qualifier directory names from the HLQ list. The specified high-level qualifier directory names are not in the existing HLQ list.

return_code

The return code from the DSFS kernel.

reason_code

The reason code.

System action

The program ends.

Administrator response:

Ensure that the high-level qualifier directory names are valid. Use commas to separate multiple high-level qualifier directory names and do not embed blanks between the names. The **dsadm configquery -hlq_list** command can be used to display the current HLQ list. To display the HLQ mode (EXCLUDE), use the **dsadm configquery -hlq_mode** command.

IDFS00326I	Successfully added the specified high-level qualifier names to the HLQ list.
Explanation: The DSFS kernel successfully added the specified high-level qualifier directory names to the HLQ list.	
System action The program ends.	
Administrator response None.	
IDFS00327I	Successfully removed the specified high-level qualifier names from the HLQ list.
Explanation: The DSFS kernel successfully removed the specified high-level qualifier directory names from the HLQ list.	
System action The program ends.	
Administrator response None.	
IDFS00328E	Missing or invalid keywords in creation parameters.
Explanation: Creation parameters require DSORG and RECFM keywords with valid data set attributes specified.	
System action The program ends.	
Administrator response: For more information about keywords for dynamic allocation, see Requesting dynamic allocation functions in <i>z/OS MVS Programming: Authorized Assembler Services Guide</i> .	
IDFS00329E	Could not set creation parameters, return code <i>return_code</i> reason code <i>reason_code</i>.
Explanation The DSFS kernel encountered an error while attempting to set the creation parameters.	
<i>return_code</i> The return code from the DSFS kernel.	
<i>reason_code</i> The reason code.	
System action The program ends.	
Administrator response: For information about the provided reason code, see Chapter 3, “Reason codes,” on page 85.	
IDFS00330E	Either the <i>-pdsmodel</i> or <i>-psmodel</i> option must be specified.
Explanation:	

Either the `-pdsmodel` or `-psmodel` option is required for the **createparm** command.

System action

The program ends.

Administrator response:

Retry the command specifying the `-pdsmodel` or `-psmodel` option.

IDFS00331E	Call to BPXWDYN encountered an error, return code <i>return_code</i>.
-------------------	--

Explanation:

BPXWDYN returned an error while attempting to verify syntax.

System action

return_code

The return code from the DSFS kernel.

System action

The program ends.

Administrator response:

For information about the provided return code, see [BPXWDYN return codes](#) in *z/OS Using REXX and z/OS UNIX System Services*.

IDFS00333E	Call to Catalog Search Interface failed with return code <i>return_code</i> and reason code <i>reason_code</i>.
-------------------	--

Explanation:

An error occurred during the call to Catalog Search Interface (CSI).

System action

return_code

The return code from CSI.

reason_code

The reason code.

System action

The program continues.

Administrator response:

Consult *z/OS DFSMS Managing Catalogs* for the displayed return code and reason code.

IDFS00334E	RACROUTE REQUEST=VERIFY call to create ACEE for user <i>user_name</i> failed with SAF rc <i>SAF_return</i> RACF rc <i>RACF_return</i> Reason Code <i>RACF_reason</i> .
------------	--

Explanation

An error occurred during the call to create an ACEE.

user name

The username.

SAF return

The SAF return code.

RACF return

The RACF return code.

RACF_reason

The RACF reason code.

System action

The program continues.

Administrator response:

Consult *z/OS Security Server RACROUTE Macro Reference* for the displayed return codes and reason code.

IDFS00335E

RACROUTE REQUEST=VERIFY call to delete ACEE ACEE for user *user_name* failed with SAF rc *SAF_return* RACF rc *RACF_return* Reason Code *RACF_reason*.

Explanation

An error occurred during the call to delete an ACEE.

ACEE

The ACEE.

user_name

The username.

SAF_return

The SAF return code.

RACF_return

The RACF return code.

RACF_reason

The RACF reason code.

System action

The program continues.

Administrator response:

Consult *z/OS Security Server RACROUTE Macro Reference* for the displayed return codes and reason code.

IDFS00336E

RACROUTE REQUEST=EXTRACT call to extract security information for user *user_name* failed with SAF rc *SAF_return* RACF rc *RACF_return* Reason Code *RACF_reason*.

Explanation

An error occurred during the call to extract a user security environment.

user_name

The username.

SAF_return

The SAF return code.

RACF_return

The RACF return code.

RACF_reason

The RACF reason code.

System action

The program continues.

Administrator response:

Consult *z/OS Security Server RACROUTE Macro Reference* for the displayed return codes and reason code.

IDFS00337E

RACROUTE REQUEST=AUTH call to authorize *access_mode* access to data set *dataset_name* for user *user_name* failed with SAF rc *SAF_return* RACF rc *RACF_return* Reason Code *RACF_reason*.

Explanation

An error occurred during the call to check user authorization to the data set.

access_mode

The access mode.

dataset_name

The data set name.

user_name

The username.

SAF_return

The SAF return code.

RACF_return

The RACF return code.

RACF_reason

The RACF reason code.

System action

The program continues.

Administrator response:

Consult *z/OS Security Server RACROUTE Macro Reference* for the displayed return codes and reason code.

IDFS00339E

Input data error storing data set *dataset_name* offset *byte_offset*: data gap larger than LRECL.

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a hole (was not written by the application) larger than the maximum record size for the data set. No new data is saved in the data set.

dataset_name

The data set name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00340E

Input data error storing data set *dataset_name(member_name)* offset *byte_offset*: data gap larger than LRECL.

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a hole (was not written by the application) larger than the maximum record size for the data set. No new data is saved in the data set.

dataset_name

The data set name.

member_name

The member name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00341E	Input data error storing data set <i>dataset_name</i> offset <i>byte_offset</i>: text record larger than LRECL.
-------------------	--

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a text record that is larger than the maximum record size for the data set. No new data is saved in the data set.

dataset_name

The data set name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00342E	Input data error storing data set <i>dataset_name(member_name)</i> offset <i>byte_offset</i>: text record larger than LRECL.
-------------------	---

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a text record that is larger than the maximum record size for the data set. No new data is saved in the data set.

dataset_name

The data set name.

member_name

The member name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00343E	Input data error storing data set <i>dataset_name</i> offset <i>byte_offset</i>: record header length larger than LRECL.
-------------------	---

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a record header that specifies a length larger than the maximum record size for the data set. No new data is saved in the data set.

dataset_name

The data set name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00344E	Input data error storing data set <i>dataset_name(member_name)</i> offset <i>byte_offset</i>: record header length larger than LRECL.
-------------------	--

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a record header that specifies a length larger than the maximum record size for the data set. No new data is saved in the data set.

dataset_name

The data set name.

member_name

The member name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00345E	Input data error storing data set <i>dataset_name</i> offset <i>byte_offset</i>: record header not equal to LRECL.
-------------------	---

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named data set but the data at the indicated offset contains a record header that specifies a length not equal to the LRECL of the fixed record data set. No new data is saved in the data set.

dataset_name

The data set name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00346E

Input data error storing data set *dataset_name(member_name)* offset *byte_offset*: record header not equal to LRECL.

Explanation

An attempt was made to store contents of the DSFS POSIX file into the named fixed record data set but the data at the indicated offset contains a record header that specifies a length not equal to the LRECL of the fixed record data set. No new data is saved in the data set.

dataset_name

The data set name.

member_name

The member name.

byte_offset

The POSIX byte offset in the file.

System action

The program continues.

Administrator response:

Update the application after reviewing the file update guidelines in [File processing](#) in *z/OS Data Set File System Administration*.

IDFS00347I

DSFS will reformat the utility file system *utility_filename*.

Explanation

The utility file system was not unmounted cleanly. It will be reformatted before use. DSFS will reformat a utility file system if there were no creation parameters set for high level qualifiers to quickly create a usable utility file system. If there were creation parameters used DSFS would perform additional actions at mount time to preserve those parameters so they are not lost.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response

None.

IDFS00348I

Linear data set *dataset_name* for DSFS utility file system *utility_filename* cannot be found or cannot be mounted.

Explanation

The named data set to be used as the utility file system does not exist or is not cataloged.

dataset_name

The data set name.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

If the UTF5_NAME option is specified in the IDFFSPRM file, change its value to a linear data set that exists. If the UTF5_NAME option is not specified, the FILESYSTEM keyword of the MOUNT command should be the uppercase name of the linear data set without its system name qualifier.

IDFS00349E

**BPXWDYN encountered an error *call_type* data set *dataset_name*,
return code *return_code*. *message_1* *message_2* *message_3* *message_4*.**

Explanation

DSFS uses the BPXWDYN service to allocate or free data sets. The error code was returned by BPXWDYN.

call_type

Type of BPXWDYN call, allocating or freeing.

dataset_name

The data set name.

return_code

The return code from the BPXWDYN call.

message_1 - message_4

Optional output messages from BPXWDYN.

System action

The program continues.

Administrator response:

For information about the provided return code, see [BPXWDYN return codes](#) in *z/OS Using REXX and z/OS UNIX System Services*.

IDFS00351A

Invalid HLQ mode *mode_setting*, DSFS initialization will stop.

Explanation

An invalid HLQ mode was specified in the DSFS parameters file. Because the HLQ mode was not valid, DSFS does not know what high-level qualifier directory names can be accessed.

mode_setting

The HLQ_MODE setting found in the DSFS parameters file.

System action

The program ends.

Administrator response:

Correct the HLQ_MODE in the DSFS parameters file. It can only be the value EXCLUDE. Restart DSFS.

IDFS00352I

DSFS is using HLQ *mode_setting* mode.

Explanation

DSFS has been initialized and is using the indicated mode for restricting which high-level qualifier directory names are allowed to be accessed by DSFS.

mode_setting

The HLQ_MODE setting used by DSFS can only be EXCLUDE.

System action

The program continues.

Administrator response

None.

IDFS00353I***mode_setting* HLQs: HLQ HLQ HLQ HLQ**

Explanation

DSFS has been initialized with the indicated list of excluded high-level qualifier directory names. This message is preceded by message IDFS00352I , which shows the HLQ mode used by DSFS.

mode_setting

The HLQ mode must be EXCLUDE.

HLQ

An high-level qualifier directory name in the HLQ_LIST provided to DSFS at initialization.

HLQ

An high-level qualifier directory name in the HLQ_LIST provided to DSFS at initialization.

HLQ

An high-level qualifier directory name in the HLQ_LIST provided to DSFS at initialization.

HLQ

An high-level qualifier directory name in the HLQ_LIST provided to DSFS at initialization.

HLQ

An high-level qualifier directory name in the HLQ_LIST provided to DSFS at initialization.

System action

The program continues.

Administrator response

None.

IDFS00354E**FILESYSTYPE PARM too long, length = *length*.**

Explanation

The FILESYSTYPE PARM is too long. The length of the specified string is provided in the message. The maximum length is 1024 characters.

In the message text:

length

The length of the string.

System action:

The program ends.

Severity:

svc_c_sev_error

Administrator Response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00355E**Error in FILESYSTYPE PARM specification *string*.**

Explanation

There is an error in the FILESYSTYPE PARM, as specified in the message.

In the message text:

string

The FILESYSTYPE PARM string.

System action:

The program ends.

Severity:

svc_c_sev_error

Administrator Response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00356E**Suffix at position *position* too long.**

Explanation

The specified suffix starting in the specified column position is too long.

In the message text:

position

The position of the error.

System action:

The program ends.

Severity:

svc_c_sev_error

Administrator Response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00357E**Comma or right paren expected at position *position***

Explanation

Either a comma or a right parenthesis should have been in the specified column position, but is not.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00358E**Suffix at position *position* not two alphanumeric chars**

Explanation

The specified suffix should be two characters long, but is not. The suffix specification should be in the specified column position.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00359E **No suffixes found at position *position***

Explanation

No valid parmlib suffix specification was found at the specified position.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00360E **No closing paren found at position *position***

Explanation

A closing parenthesis was not found where one was expected, in the specified column position.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00361E **No open paren found at position *position***

Explanation

Parmlib suffix specifications require parentheses around them. There is no opening parenthesis found. It is expected in the specified column position.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00362E**No equals sign found at position *position*****Explanation**

Parmlib suffix specifications require an equals sign. It is expected in the specified column position.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00363E**Extra characters were found at position *position*****Explanation**

Extra characters are not allowed. They start in the specified column.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00364E**PRM not found at position *position*****Explanation**

No PRM was found for parmlib suffix specifications. It is expected in the specified column.

In the message text:

position

The position of the error.

System action

The program ends.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

IDFS00365E**Media Manager return code *return_code* disconnecting utility file system *utility_filename*.****Explanation**

The return code for the Media Manager disconnect was nonzero for the specified utility file system. This might occur during a failed mount or during an unmount of the specified utility file system.

In the message text:

return_code

The hexadecimal Media Manager return code.

utility_filename

The utility file system name.

System action

The program continues.

Administrator response:

Correct the problem and restart DSFS. If the problem persists, or there is no error, contact your service representative.

Chapter 3. Reason codes

Reason codes are listed by hexadecimal value and include a description of the action required to correct the error. Each reason code is made up of four bytes, `cccc rrrr`, where `cccc` is a halfword reason code qualifier and `rrrr` is the halfword reason code.

The two high-order bytes of the reason codes that are returned contain a value that is used to qualify the contents of the two low-order bytes. Reason code qualifiers for DSFS are found within the range 'ED01' -X'EDFF'.

6000	One or more required parameters are missing.
Action: Specify the required number of parameters.	
6001	Command is too long. Its length exceeds maximum length of 256 characters.
Action: Enter a command that is less than 256 characters.	
6002	Internal parsing error.
Action: Contact the service representative.	
6003	Too many parameters specified.
Action: Enter the command specifying fewer parameters.	
6004	Two or more mutually exclusive parameters used.
Action: Enter the command with one of the parameters, not both.	
6005	The command was entered with too few arguments.
Action: Specify the minimum number of arguments.	
6006	Unrecognized or ambiguous command name.
Action: Enter the command again specifying a valid unabbreviated command.	
6007	The command parameter requires an argument value that is missing.
Action: Specify a valid argument value.	
6008	Unrecognized or ambiguous parameter switch name.
Action: Enter the command again with a valid parameter.	
6009	Defined parameters exceed the maximum.
Action: Contact the service representative.	
600A	Unable to find appropriate commands.
Action: Contact the service representative.	

600B	Hi-used-RBA is more than hi-allocated-RBA. This should be compared with the TSO LISTCAT command.
Action: Contact the service representative.	
600D	The buffer is not valid.
Action: Contact the service representative.	
6013	An invalid program module format was encountered.
Action: If the target data set is a PDS, check that the program module is not a program object with structures that are specific to program objects. Otherwise, check that the source file is a valid program module.	
6015	Internal error - could not access a directory block.
Action: Contact the service representative.	
6016	Internal failure during start transaction operation.
Action: An internal failure occurred. Contact the service representative.	
6017	Attempt to delete a non-empty directory.
Action: Ensure that the directory is empty before attempting to remove it.	
6018	Internal error updating mtime or ctime.
Action: If the utility file system is disabled, ensure it is remounted after DSFS restarts. Retry the operation. If the problem persists, contact the service representative.	
601B	Error attempting to remove a name from a directory.
Action: Ensure that you are not attempting to remove the . or . . entry from the directory, and try the operation again.	
601C	Non-critical I/O wait failure.
Action: Contact the service representative.	
601D	The log/buffer package was reinitialized.
Action: Contact the service representative.	
601F	An abend occurred in the security product while processing this operation.
Action: Try to determine the cause of the security product failure, correct it, and then retry the operation. If the problem persists, contact the service representative.	
6020	Failure getting index on volstat.
Action: Contact the service representative.	
6021	Name not found in HLQ list.
Action: Ensure that the name entered matches the desired HLQ directory name and retry the request. If the problem persists, contact your service representative.	

6022	File System has been deleted.
Action: Contact the service representative.	
6024	Could not create a new admin thread.
Action: Contact the service representative.	
6025	Internal failure during thread pool configuration.
Action: An internal failure occurred. Contact the service representative.	
6026	Internal failure in wait service.
Action: An internal failure occurred. Contact the service representative.	
6027	Thread pool size cannot be smaller than the required minimum. If dynamically changing the pool size, the new size cannot be smaller than the old size.
Action: Specify a configuration option value of 1 or greater. If dynamically changing the pool size, you can only specify a new size larger than the old size.	
6028	Too many threads attempted.
Action: Specify a configuration option value of 1000 or less.	
6029	Unable to get storage to perform the requested operation.
Action: Make more space available and reissue the request.	
602C	File system not found.
Action: Contact the service representative.	
602E	Internal failure. File system name not unique.
Action: Contact the service representative.	
602F	Internal Failure. File system name not found.
Action: Contact the service representative.	
6031	Internal failure. Mount name not found.
Action: Contact the service representative.	
6034	Internal failure.
Action: An internal failure occurred. Contact the service representative.	
6036	The new value specified is not allowed, or is not correct.
Action: Correct the new value and try the operation again.	
6037	Could not set the parm value as requested.
Action:	

An internal failure occurred. Contact the service representative.

6038	The edcfixd option was specified with filecache_size, but the file cache pages cannot be registered with the zEDC Express service.
-------------	---

Action:

If the zEDC Express service is not available, ensure that the edcfixd option is not used with the filecache_size option in the IDFFSPRM member. Also, ensure that it is not used with the **dsadm config -filecache_size** command.

6039	Invalid parm to afscall_config.
-------------	--

Action:

An internal failure occurred. Contact the service representative.

603A	Internal failure. File cache not initiated.
-------------	--

Action:

An internal failure occurred. Contact the service representative.

603E	Another thread pool resize command is already in progress.
-------------	---

Action:

Try the command again when no thread pool resize is in progress. If the problem persists, contact the service representative.

603F	CFG_OPTION structure invalid.
-------------	--------------------------------------

Action:

Correct the CFG_OPTION structure.

6040	The threshold,increment pair is invalid. Each value in the pair must be in the range 1 to 99.
-------------	--

Action:

Correct the value and try the operation again.

6042	Failed to set or resize the EDC_BUFFER_POOL due to zEDC error.
-------------	---

Action:

Check error message IDFS00288E to see the zEDC return code and reason code. Fix the error and try again.

6043	Unexpected error resizing the pool used for encryption and compression.
-------------	--

Action:

Contact the service representative.

6047	An error was encountered.
-------------	----------------------------------

Action:

Contact the service representative.

6048	One or more arguments are not valid.
-------------	---

Action:

Contact the service representative.

6049	Event already in set.
-------------	------------------------------

Action:

Contact the service representative.

604A	There is no available space on the log device.
-------------	---

Action:

Contact the service representative.

604F	The specified buffer could not be deleted.
-------------	---

Action:

Contact the service representative.

6050	The requested operation would block.
-------------	---

Action:

Contact the service representative.

6051	The specified transaction is not valid.
-------------	--

Action:

Contact the service representative.

6052	The specified transaction is active.
-------------	---

Action:

Contact the service representative.

6054	The specified transaction has completed.
-------------	---

Action:

Contact the service representative.

6055	The specified transaction has committed.
-------------	---

Action:

Contact the service representative.

6056	An error occurred setting state during utility file system mount.
-------------	--

Action:

Contact the service representative.

6057	Recovery is complete.
-------------	------------------------------

Action:

Contact the service representative.

6058	Incorrect utility file system handle.
-------------	--

Action:

Contact the service representative.

6059	Incorrect anode handle.
-------------	--------------------------------

Action:

Contact the service representative.

605A	Index is out of range or anode is not valid.
-------------	---

Action:

Contact the service representative.

605C	Incorrect, undefined or inconsistent command value.
-------------	--

Action:

Contact the service representative.

605E	Fid unique identifier does not match.
-------------	--

Action:

Contact the service representative.

6060	Incorrect volume handle.
-------------	---------------------------------

Action:

Contact the service representative.

6061	File cannot have negative link count.
-------------	--

Action:

Contact the service representative.

6064	Block is past the allocated end of the container.
Action: Contact the service representative.	
6065	Block address is too large.
Action: Contact the service representative.	
6067	A transaction must be specified.
Action: Contact the service representative.	
6068	Block is interior to the container but is not allocated.
Action: Contact the service representative.	
6069	Specified anode index does not exist.
Action: Contact the service representative.	
606A	The anode does not contain a file.
Action: Contact the service representative.	
606B	The container does not contain a volume table.
Action: Contact the service representative.	
606C	The bitmap is not consistent with the superblock.
Action: Contact the service representative.	
606D	The superblock does not lead to an AVL.
Action: Contact the service representative.	
606E	The file does not point to a createparm container.
Action: Contact the service representative.	
606F	Container is stored inline or fragmented.
Action: Contact the service representative.	
6070	Container is stored inline or blocked.
Action: Contact the service representative.	
6071	Container is stored fragmented or blocked.
Action: Contact the service representative.	
6072	An anode being deleted is still open.
Action: Contact the service representative.	
6073	An anode is not empty.

Action:

Contact the service representative.

6074	Other containers using these blocks for copy-on-write purposes.
-------------	--

Action:

Contact the service representative.

6075	Read operation extends past container length.
-------------	--

Action:

Contact the service representative.

6076	Specified size of the status area is too large.
-------------	--

Action:

Contact the service representative.

6077	Insufficient space on volume.
-------------	--------------------------------------

Action:

Contact the service representative.

6078	Copy-on-write is not available for this container.
-------------	---

Action:

Contact the service representative.

6079	Block allocation of log is in error.
-------------	---

Action:

Contact the service representative.

607A	Block allocation for bitmap ended in error.
-------------	--

Action:

Contact the service representative.

607D	Initialization entry point called more than once.
-------------	--

Action:

Contact the service representative.

607E	Object or module not properly initialized.
-------------	---

Action:

Contact the service representative.

607F	Tried to insert a block that is already allocated.
-------------	---

Action:

Contact the service representative.

6080	Incorrect block insertion parameters.
-------------	--

Action:

Contact the service representative.

6081	A rock was specified whose value was zero.
-------------	---

Action:

Contact the service representative.

6082	A volume was referenced while going offline.
-------------	---

Action:

Contact the service representative.

6083	An utility file system was referenced while going offline.
-------------	---

Action:

Contact the service representative.

6084	The container does not contain a volume header.
Action: Contact the service representative.	
6085	Volume does not have a root directory.
Action: Contact the service representative.	
6088	Write operation encountered an inconsistent state.
Action: Contact the service representative.	
6089	Existing fragment group cannot be extended.
Action: Contact the service representative.	
608A	Utility file system has some open volumes.
Action: Contact the service representative.	
608B	Volume has some open anodes.
Action: Contact the service representative.	
608D	New length is inconsistent with storage method.
Action: Contact the service representative.	
608E	Iterator value indicates previous is last.
Action: Contact the service representative.	
608F	Aux type inappropriate for non-directory files.
Action: Contact the service representative.	
6090	Anode block and offset pair is not valid.
Action: Contact the service representative.	
6092	Could not obtain a vnode due to vnode cache maximum size being reached.
Action: Contact the service representative.	
6093	File is deleted from system.
Action: Contact the service representative.	
6094	Could not use the edcfixed option to fix the file cache. The edcfixed option is limited to 14GB file caches or less.
Action: Either make the file cache smaller or do not specify the edcfixed option.	
6095	Failed to set or resize the file cache due to page fix error.
Action: Check for error message IDFS00288E to see the zEDC return code and reason code. Fix the error and try again.	

6096	Attempt to make the file cache too small.
Action: Specify a configuration option FILECACHE_SIZE value of 10M or greater.	
6097	File cache size too big.
Action: Ensure that the -filecache_size value specified is less than 65536M.	
6098	Guardtime check on setattr failed.
Action: Contact the service representative.	
6099	Internal error. File cache has bad page pointers.
Action: Contact the service representative.	
609A	Internal error. File cache has bad page counts.
Action: Contact the service representative.	
609B	Internal error. Scheduling of dirty data from file cache failed.
Action: Contact the service representative.	
609C	Internal error. Sync of pending IO from file cache failed.
Action: Contact the service representative.	
609D	Internal error. Could not truncate file in file cache.
Action: Contact the service representative.	
609E	Internal error resizing file cache.
Action: Contact the service representative.	
609F	Internal error reading a file into the file cache.
Action: Contact the service representative.	
60A0	Internal error writing a file from the file cache.
Action: Contact the service representative.	
60A1	Internal error getting attributes for a file in the file cache.
Action: Contact the service representative.	
60A2	Internal error scheduling file data at close from the file cache.
Action: Contact the service representative.	
60A3	Internal error when doing fsync of file data from the file cache.
Action: Contact the service representative.	
60A4	Internal error setting file attributes in file cache.

Action:

Contact the service representative.

60A5	Internal error handling page faults in file cache.
-------------	---

Action:

Contact the service representative.

60A8	Internal error freeing cache data from file cache.
-------------	---

Action:

Contact the service representative.

60A9	Internal error obtaining file block information for a file in the file cache.
-------------	--

Action:

Contact the service representative.

60AB	The utility file system log could not be recovered.
-------------	--

Action:

Contact the service representative.

60AD	Error creating or writing new utility file system structures.
-------------	--

Action:

Contact the service representative.

60AE	Disk sizes too small.
-------------	------------------------------

Action:

Contact the service representative.

60AF	A key label was specified but ICSF is not running.
-------------	---

Action:

Ensure that ICSF is running and try the command again.

60B0	Internal failure during ifs_close.
-------------	---

Action:

An internal failure occurred. Contact the service representative.

60B5	Error initializing the device.
-------------	---------------------------------------

Action:

Contact the service representative.

60B6	Utility file system is already formatted.
-------------	--

Action:

Contact the service representative.

60B7	File system partition too small.
-------------	---

Action:

Contact the service representative.

60B8	Too few disk blocks for file system.
-------------	---

Action:

Contact the service representative.

60B9	DFSMS returned an error while opening a utility file system.
-------------	---

Action:

See messages IDFS00290E and IEC161I at the console for more information.

60BA	An attempt to format a utility file system for encryption failed because the utility file system data set is not eligible for encryption.
-------------	--

Action:

Refer to the section on defining the encryption management mechanism in *z/OS DFSMSdfp Storage Administration* for information about how to define the data set in an SMS class that is eligible for encryption and that has a valid assigned key label.

60BB	Cannot open VSAM Linear Data Set for format.
Action:	Ensure the VSAM Linear Data Set exists and is accessible before retrying the operation.
60BC	Anode open failed.
Action:	Contact the service representative.
60BD	Unexpected error attaching newly created utility file system.
Action:	Contact the service representative.
60BE	Device does not exist.
Action:	Contact the service representative.
60BF	Internal failure during remove operation.
Action:	Contact the service representative.
60C0	Could not create an entry in a directory.
Action:	Contact the service representative if the return code is EMVSERR (157).
60C1	Internal error getting the status for a vnode.
Action:	Contact the service representative.
60C3	Internal failure during vnode lookup operation.
Action:	An internal failure occurred. Contact the service representative.
60C6	Setattr truncation error.
Action:	Contact the service representative.
60C8	Attempt to truncate a directory, not allowed.
Action:	Ensure that you are not attempting to truncate a directory.
60C9	Timestamp too large for 5 bytes.
Action:	Cannot store a timestamp that is larger than 5 bytes.
60CA	Unexpected error searching a directory.
Action:	Contact the service representative.
60CB	No vnode found for FID.
Action:	This reason code, when coupled with a return code of ENOENT, simply means that an operation was presented to DSFS for a previously deleted file. If a different return code is presented, then contact the service representative.

60CC	A required name entry in a directory was not found.
Action: If the return code is 129 (ENOENT), correct the directory name and try again. Otherwise, contact the service representative.	
60CD	A lookup attempted on an object that was not a directory.
Action: Ensure that the name containing the object being looked up is a directory.	
60CF	A write operation was attempted against a directory with a corrupted tree.
Action: Contact the service representative.	
60D0	Creating a dir on vn_create.
Action: Contact the service representative.	
60D1	A bad vnode/anode pointer state exists.
Action: Internal error. Contact your service representative.	
60D2	Incorrect file handle.
Action: Contact the service representative.	
60D3	Internal error setting vnode key.
Action: Contact the service representative.	
60D4	Internal error creating the utility file system.
Action: Contact the service representative.	
60D5	Error creating root directory in a new utility file system.
Action: Contact the service representative.	
60D6	Error adding file system to utility file system file system table on disk.
Action: Contact the service representative.	
60DB	Could not reinitialize a new vnode after a utility file system operation.
Action: Contact the service representative.	
60DC	Could not initialize a vnode.
Action: If the utility file system is disabled, ensure unmount and remount of the utility file system after DSFS is restarted. Retry the operation. If the problem persists, contact the service representative.	
60DD	Internal error trying to place a hold on a vnode.
Action: Contact the service representative.	
60DE	Could not initialize a new vnode due to anode handle create failure.
Action:	

Contact the service representative.

60DF	File truncate error.
-------------	-----------------------------

Action:

Contact the service representative.

60F0	Specified anode index already exists.
-------------	--

Action:

Contact the service representative.

60F1	Supplied status data extends too far.
-------------	--

Action:

Contact the service representative.

60F2	Insufficient space on utility file system.
-------------	---

Action:

Ensure that there is sufficient space on the utility file system.

60F3	Internal failure during item create.
-------------	---

Action:

Contact the service representative.

60F4	Internal failure during zlc.
-------------	-------------------------------------

Action:

Contact the service representative.

60FA	File System is out of service.
-------------	---------------------------------------

Action:

Contact the service representative.

60FB	File System is damaged.
-------------	--------------------------------

Action:

Contact the service representative.

60FD	An error was encountered processing the zero link count list.
-------------	--

Action:

Contact the service representative.

60FE	The GRS concurrent ENQ limit has been reached.
-------------	---

Action:

Increase your systems concurrent limit to ensure proper functionality.

60FF	An internal error was encountered during a GRS ENQ call.
-------------	---

Action:

Contact the service representative.

6100	Internal failure during utility file system operation.
-------------	---

Action:

An internal failure occurred during a utility file system operation. Contact the service representative.

6101	Detach failed because some utility file systems could not be closed.
-------------	---

Action:

Contact the service representative.

6102	Unmount of utility file system cannot proceed.
-------------	---

Action:

Contact the service representative.

6103	Detach cannot proceed because utility file system is quiesced.
Action:	Unmount the utility file system after the operation causing the quiesce has completed.
6104	Utility file system being formatted
Action:	Wait for the format of the utility file system to complete, and try the unmount operation again.
6105	The file system on the utility file system could not be opened.
Action:	Contact the service representative.
6106	Internal problem with the utility file system that is preventing it from being mounted.
Action:	Ensure that the utility file system has been successfully formatted. Otherwise, contact the service representative.
6109	Formatting an attached utility file system.
Action:	Contact the service representative.
6116	The AGGR_FORMAT structure has invalid values.
Action:	Contact the service representative.
6117	The name of the utility file system being formatted is invalid.
Action:	Contact the service representative.
6118	Unexpected error growing utility file system.
Action:	You may have a zero secondary allocation on the data set or there may not be sufficient space on the volume. Otherwise, contact the service representative.
6119	Container does not have an allocation handle.
Action:	Contact the service representative.
611A	Incorrect, undefined or inconsistent arguments.
Action:	Contact the service representative.
611B	An error occurred during extension of the DSFS utility file system.
Action:	DFSMS failed the extension attempt. The DFSMS return code is returned in the second byte of the return code. The DFSMS Problem Determination Function (PDF) code is returned in the third byte of the return code. The meaning of these codes can be determined by looking at message IEC161I.
611C	Could not determine status of the utility file system.
Action:	Contact the service representative.
611D	File system not locally mounted on owning system.
Action:	Retry operation after file system is mounted.

611E	Aggregate not found.
Action: The utility file system specified cannot be found. Correct the utility file system name and try again.	
6120	Salvage found minor errors in the utility file system. The utility file system is marked damaged and DSFS restarted. The utility file system will be reformatted the next time it is mounted.
Action: If the problem persists, contact the service representative.	
6121	There is no salvage operation to cancel. The utility file system is not currently being salvaged.
Action: If the utility file system is being salvaged, contact the service representative.	
6124	Salvage found major errors in the utility file system. The utility file system is marked damaged and DSFS restarted. The utility file system will be reformatted the next time it is mounted.
Action: If the problem persists, contact the service representative.	
6127	A long-running operation was interrupted by an unmount, a file system shutdown command, or a cancel command. This is normal for long-running operations.
Action: To continue the long-running operation, you will need to restart it.	
6128	Utility file system sync operation failed.
Action: Contact the service representative.	
6129	Utility file system already quiesced or quiescing, or unquiescing.
Action: The utility file system is already quiesced or a quiesce or unquiesce operation is already in progress for this utility file system. If utility file system is being dynamically grown, the utility file system should not be already quiesced. Contact the service representative.	
612A	Utility file system is busy. It cannot perform the operation requested.
Action: The utility file system is busy with another operation that conflicts with this operation. Try your request again. If it continues to fail, contact the service representative.	
612B	The command failed because the utility file system is disabled. A utility file system can be disabled due to an I/O error, an internal DSFS error, or a data set reopen operation fails. If the utility file system is encrypted, this can be caused by ICSF problems. DSFS will attempt to restart.
Action: If the utility file system is encrypted, correct any ICSF problem so the utility file system can be remounted. When the utility file system is remounted, try the command again. If the problem persists, contact the service representative.	
612C	Error closing utility file system.
Action: Contact the service representative.	
612D	Utility file system busy with another operation.

Use the error code to determine why the file system could not be quiesced during the utility file system quiesce.

Action:

Action:

Action:

Action:

Action:

Action:

Action:

Action:

Action:

Action:

Action:

Action:

Action:

100 z/OS: z/OS Data Set File System Messages and Codes

6141	AGGR_FORMAT reserved field invalid.
Action:	Contact the service representative.
6142	Either you are not properly authorized for this operation or DSFS could not verify your authorization. The subcommand requires UPDATE access to the utility file system.
Action:	Ensure that the proper access is granted and try the operation again.
6144	The key label specified is not associated with an encryption type supported by DFSMS.
Action:	Specify another key label and try the command again.
6145	ICSF returned an error while validating a key label.
Action:	Take the action documented in message IDFS00285E.
6146	ICSF could not find the specified key label.
Action:	A key label must be known to ICSF before it can be used when defining or encrypting a DSFS utility file system.
614A	z/OS UNIX System Services routine osi_ctl encountered an error.
Action:	Contact the service representative.
614B	Internal failure.
Action:	An internal failure occurred. Contact the service representative.
614C	Invalid parms in request.
Action:	An invalid parameter was passed. Correct the parameter and try again.
614D	A utility file system with a key label cannot be mounted because ICSF is not initialized.
Action:	Ensure ICSF is initialized and try the command again.
614E	The mount fails because zEDC is not initialized. The utility file system is compressed and requires zEDC to be ready before it can be mounted on this system.
Action:	Try the operation again after zEDC is initialized.
614F	Internal failure during mount operation.
Action:	An internal failure occurred during a mount operation. Contact the service representative.
6150	SVC 26 Listcat call returned an error.
Action:	Verify that the data set exists. Try issuing Listcat against the data set.
6151	Incorrect utility file system name or catalog errors.
Action:	

Check the system log for messages indicating there is a catalog error. If none are found, contact the service representative.

6152 Internal failure completing asynchronous mount operation.

Action:

An internal failure occurred during a mount operation. Contact the service representative.

6153 Internal failure during mount operation.

Action:

An internal failure occurred during a mount operation. Contact the service representative.

6154 The MOUNT command was specified with DSFS mount parameters. Mount parameters are not supported for DSFS.

Action:

Remove the mount parameters from the MOUNT command and issue the command again.

6155 Error parsing FSFULL parameter in IDFFSPRM file.

Action:

Ensure that the syntax of the FSFULL option in the IDFFSPRM file is valid.

6156 Attempt to mount a utility file system read-only is not allowed.

Action:

Ensure that the utility file system that is being mounted read-write, and try the mount again.

6159 No root directory found for file system.

Action:

You may need to define a new utility file system. See *z/OS Data Set File System Administration* for information about managing utility file systems. Contact the service representative.

615A File system busy or unable to be mounted. DSFS only allows one mounted file system.

Action:

There is another operation in progress that conflicts with this operation. If there are no mounted file systems after the conflict is resolved, try your request again. If it continues to fail, contact the service representative.

615B Lookup failure for volser for utility file system attach.

Action:

Contact the service representative.

615E Could not obtain ENQs indicating utility file system ownership.

Action:

Contact the service representative.

6160 Utility file system already attached.

Action:

Contact the service representative.

6162 Striped VSAM Linear Data Set not supported for DSFS utility file system.

Action:

Striped VSAM Linear Data Sets are not supported. If the VSAM LDS was not defined as striped, contact the service representative.

6163 Error with issuing a LOCATE call for a utility file system.

Action:

If the UTF5_NAME option in the IDFFSPRM file is specified, ensure the value is the full name of the VSAM linear data set. Otherwise, ensure that the file system named on the MOUNT command has the same name as the VSAM linear data set to be used as the utility file system, minus the last qualifier (which must be the system

name). Also ensure that the file system named on the MOUNT command is in uppercase. You can also check the system log for catalog errors. If the problem persists, contact the service representative.

6164 Utility file system is not a VSAM Linear Data Set.

Action:

Ensure that the utility file system data set is defined as a VSAM Linear Data Set. If the problem persists, contact the service representative.

6165 Error attaching utility file system.

Action:

A mount of a DSFS file system that fails with return code 138 (ENXIO) can indicate that the file system is already mounted on another system that is not in the same sysplex but is sharing DASD accessibility. DSFS prevents data corruption by not allowing a DSFS file system to be mounted read-write on two systems that are not in a shared file system environment. In this case, verify that the file system is not already mounted read-write on another system. DSFS prevents a system from writing to a DSFS utility file system that is mounted read-write on another system. Another possible cause is the VSAM linear data set was not correctly formatted. Also, look in the system log for messages from other z/OS components related to this utility file system (data set) name. Otherwise, contact the service representative.

6166 Statistics Query Parm0 value is invalid.

Action:

The Parm0 value for all Statistics Query subcommands must be 32.

6167 Statistics Query Parm1 value is invalid.

Action:

The Parm1 value for all Statistics Query subcommands must be 80.

6169 Syscall_parmlist bad offset at parms1.

Action:

The STAT_API structure must be 48 bytes. The offset at parms1 must be 80 (32+48).

616B Reserved bytes must be zero.

Action:

The sa_reserve bytes in the STAT_API must be zeros.

616C No thread available for the requested long-running command.

Action:

Retry the request when there is an available thread for the long-running command.

616D STAT_API eye catcher is wrong.

Action:

The eyecatcher for the STAT_API structure must be STAP.

616E STAT_API version number is wrong.

Action:

The version number for the STAT_API structure must be 1 or 2.

616F STAT_API size is wrong.

Action:

The size of the STAT_API structure must be at least 48 bytes.

6170 Buffer size is too small.

Action:

The size of the buffers for a statistics query were not large enough.

6172 Report type is wrong.

Action:

The statistics subcommand is invalid.

6174	Statistics Locking Query Parm0 value is invalid.
Action: The Parm0 value for the Statistics Locking Query subcommand must be 32.	
6175	Statistics Storage Query Parm0 value is invalid.
Action: The Parm0 value for the Statistics Storage Query subcommand must be 32.	
6176	Statistics Locking Query Parm1 value is invalid.
Action: The Parm1 value for the Statistics Locking Query subcommand must be 80.	
6177	Statistics Storage Query Parm1 value is invalid.
Action: The Parm1 value for the Statistics Storage Query subcommand must be 80.	
617C	Statistics Iobydasd Query Parm0 value is invalid.
Action: The Parm0 value for the Statistics Iobydasd Query subcommand must be 32.	
617D	Statistics Iobydasd Query Parm1 value is invalid.
Action: The Parm1 value for the Statistics Iobydasd Query subcommand must be 80.	
618C	The security server could not return a UTOKEN for the user.
Action: Internal error. Contact the service representative.	
618D	The caller is not UID 0.
Action: Ensure that you are properly authorized for this operation. This subcommand requires UID 0 or READ access to the SUPERUSER.FILESYS.PFSCCTL profile in the z/OS UNIXPRIV class.	
618E	Invalid PFS control request command.
Action: Ensure that the application is specifying a valid pfscctl request.	
618F	Utility file system name longer than 44 characters. The utility file system name is the name that is specified in the UTFS_NAME option of the IDFFSPRM file or the name that is the result of combining the FILESYSTEM parameter on the mount command with the local system name.
Action: Change the utility file system name to be 44 characters or less.	
6196	Version number is incorrect.
Action: Contact the service representative.	
6197	The eye catcher is incorrect.
Action: Contact the service representative.	
6198	The value in the er_flags field must be hex zero.
Action: Contact the service representative.	

6199	The value in the er_fill field must be hex zeros.
Action: Contact the service representative.	
619A	The values in the er_reserve fields must be hex zeros.
Action: Contact the service representative.	
619B	The -filename parameter was too long.
Action: Contact the service representative.	
619C	The -path parameter was too long.
Action: Contact the service representative.	
619D	The -msg parameter was too long.
Action: Contact the service representative.	
619E	The -filesystem name parameter was too long.
Action: Contact the service representative.	
619F	PFS control command failed.
Action: Check the return code to determine why the pfsctl function failed.	
61A0	Failed obtaining data from the user buffer.
Action: Contact the service representative.	
61A1	Failed writing data into the user buffer.
Action: Contact the service representative.	
61A3	Length for parm0 is bad.
Action: Fix the length and retry.	
61A4	Length for parm1 is bad.
Action: Fix the length and retry.	
61A5	Length for parm2 is bad.
Action: Fix the length and retry.	
61A6	Length for parm3 is bad.
Action: Fix the length and retry.	
61A7	Length for parm4 is bad.
Action: Fix the length and retry.	
61A8	Length for parm5 is bad.

Fix the length and retry.

61A9

Length for parm6 is bad.

Fix the length and retry.

61AB

Internal error while processing FSINFO request.

Contact the service representative.

61AC

There are too many in-progress PFCTL commands.

DSFS has reached its limit of concurrent PFSCtl calls. This is generally not typical. Contact the service representative.

61AD

Bad parameter value passed in FSINFO_REQUEST structure.

Correct the bad parameter and retry the operation.

61AE

Parms0 is not zero.

The offset at parms0 must be set to zero.

61AF

Parms1 is not set to zero.

The offset at parms1 must be set to zero.

61B0

Parms2 is not set to zero.

The offset at parms2 must be set to zero.

61B1

Parms3 is not set to zero.

The offset at parms3 must be set to zero.

61B2

Parms4 is not set to zero.

The offset at parms4 must be set to zero.

61B3

Parms5 is not set to zero.

The offset at parms5 must be set to zero.

61B4

Parms6 is not set to zero.

The offset at parms6 must be set to zero.

61BB

syscall_parmlist bad offset at parm4.

Specify the correct offset in parm4.

61BC

syscall_parmlist parm4 truncated.

Specify a size to include all the parms.

61BD

syscall_parmlist parm4 missing.

Action:

Specify parm4.

61BE **A Syscall parmlist is invalid.**

Action:

Provide a valid subcommand opcode or ensure the argument is large enough to hold the syscall parmlist.

61BF **Syscall_parmlist bad offset at parm0.**

Action:

The offset at parms0 must be 32.

61C0 **Syscall_parmlist parms0 truncated.**

Action:

The pfsctl argument must be increased to contain the entire required argument.

61C1 **Syscall_parmlist parms0 missing.**

Action:

A nonzero parms0 must be specified.

61C2 **Syscall_parmlist bad offset at parms1.**

Action:

The offset at parms1 must contain the correct offset for the required parameters.

61C3 **Syscall_parmlist parms1 truncated.**

Action:

The pfsctl argument must be increased to contain the entire required argument.

61C4 **Syscall_parmlist parms1 missing.**

Action:

A nonzero parms1 must be specified.

61C5 **Syscall_parmlist bad offset at parms2.**

Action:

The offset at parms2 must contain the correct offset for the required parameters.

61C6 **Syscall_parmlist parms2 truncated.**

Action:

The pfsctl argument must be increased to contain the entire required argument.

61C7 **Syscall_parmlist parms2 missing.**

Action:

A nonzero parms2 must be specified.

61C8 **Syscall_parmlist bad offset at parms3.**

Action:

The offset at parms3 must contain the correct offset for the required parameters.

61C9 **Syscall_parmlist parms3 truncated.**

Action:

The pfsctl argument must be increased to contain the entire required argument.

61CA **Syscall_parmlist parms3 missing.**

Action:

A nonzero parms3 must be specified.

61CB **Syscall_parmlist unexpected opcode.**

Action:

Provide a valid subcommand opcode.

61CC	Syscall_parmlist unexpected command.
Action: Provide a valid DSFS pfsctl command.	
61CD	Vget failure not yet reported.
Action: Contact the service representative.	
61CE	Error returned from volStat function.
Action: Contact the service representative.	
61CF	The VSAM LDS is not formatted, is not marked as intended for DSFS, and cannot be formatted during mount.
Action: Ensure that the VSAM LDS is defined using the ZFS keyword. If it does not automatically format during mount, contact the service representative.	
61D2	Error from osi_getvnode token.
Action: Contact the service representative.	
61D3	Failed obtaining request block for cross memory call.
Action: Contact the service representative.	
61D4	Internal failure during a lock operation.
Action: Contact the service representative.	
61D5	Error from osi_getvnode.
Action: Contact the service representative.	
61D6	Readdir error.
Action: Contact the service representative.	
61D7	Buffer size is 0 on a readdir attempt.
Action: Ensure that the readdir buffer size is larger than 0.	
61D8	Could not open anode for vnode.
Action: This could occur if a task was trying to open a file that was removed by another task at the same time. It can also occur if there was a recent system or DSFS outage. If however, it repeatedly occurs and a recent system outage did not occur, then contact the service representative.	
61D9	Vnode is unusable, possibly due to an outage/restart of DSFS on a system.
Action: Try restarting the application, if that fails to correct the problem then try remounting the utility file system.	
61DA	General vn_remove error.
Action: Contact the service representative.	

61DD	Target of rename is a directory that was not empty.
Action:	Ensure that the directory that is the target of a rename is empty.
61DE	Try to remove link from a directory, not allowed.
Action:	Ensure that the path name is not a directory.
61DF	Rmdir error.
Action:	Contact the service representative.
61E0	General rename error.
Action:	Contact the service representative.
61E1	Directory operation on a vnode that is not a directory.
Action:	Contact the service representative.
61E3	Error looking up a file.
Action:	Ensure the object exists. If it does, contact the service representative.
61E5	Error on mkdir request.
Action:	Contact the service representative.
61E6	Operation failed to get vnode token in a directory.
Action:	Contact the service representative.
61E7	Create failure.
Action:	Contact the service representative.
61E9	An invalid command code was requested.
Action:	Correct the invalid command code and retry.
61EA	The input FOBJ_INFO buffer is invalid.
Action:	The application must provide a buffer large enough to hold an FOBJ_INFO structure, have the proper eye catcher set in the structure, a proper version field, and a length field that is at least as large as the FOBJ_INFO structure.
61EB	File System operation in progress.
Action:	Contact the service representative.
61EC	General VM cache failure.
Action:	If the return code is ENOSPC (133), the file system or utility file system is full. If this is the case, make more space available. Otherwise, contact the service representative.
61ED	Write past largest supported DSFS file size or past the file allocation limit, which includes space for file location maps.
Action:	

Remove data from the file to make room for the new data, or write the new data to another file.

61EE	Process limit was exceeded on write request.
-------------	---

Action:

Ensure that the user is not attempting to exceed the process file size limit.

61EF	Process limit was exceeded because it was not allowed to increase size of file.
-------------	--

Action:

Ensure that you are not attempting to exceed the process file size limit.

61F0	An open file lost some updates due to a DSFS crash.
-------------	--

Action:

Contact the service representative.

61F1	Internal failure obtaining memory for operation.
-------------	---

Action:

An internal failure occurred. Contact the service representative.

61F2	General setattr error.
-------------	-------------------------------

Action:

Contact the service representative.

61F3	File sync error.
-------------	-------------------------

Action:

Contact the service representative.

61F7	Error truncating file during open.
-------------	---

Action:

Contact the service representative.

61F8	Access failure.
-------------	------------------------

Action:

Contact the service representative.

61F9	A write operation to a read-only file system.
-------------	--

Action:

The utility file system can only be mounted read-write. Contact the service representative.

61FA	Failure getting attr specified in OSI struct.
-------------	--

Action:

Contact the service representative.

61FB	Invalid operation on a zero-link count vnode.
-------------	--

Action:

Ensure that the object still exists. If it does, contact your service representative.

61FC	The operation failed due to a disabled utility file system. A utility file system can be temporarily disabled due to an I/O error, an internal DSFS error, or a data set reopen operation fails. If the utility file system is encrypted, this can be caused by ICSF problems. File requests will fail while the utility file system is disabled. DSFS will attempt to restart.
-------------	--

Action:

If the utility file system is encrypted, correct any ICSF problem so the utility file system can be re-enabled. Ensure DSFS is restarted and the utility file system remounted. The file can be closed and reopened and the request can be attempted again.

61FD	UNIX System Services has supplied invalid input to DSFS.
Action:	UNIX System Services should have taken a diagnostic dump. If not, obtain a dump of UNIX System Services using SLIP on the reason code as documented in <i>z/OS UNIX System Services Messages and Codes</i> , and then contact the service representative.
61FE	Unable to establish the recovery environment.
Action:	Ensure that the DSFS Physical File System is started. If it is active and the error still occurs, contact the service representative.
61FF	Uiomove failed, probably due to user address space errors.
Action:	Contact the service representative.
6200	The data set is not a VSAM linear data set.
Action:	Define the VSAM data set as linear and then retry the operation.
6201	Recovery routine given control.
Action:	The user has been canceled or has issued CTRL-escape. The operation has completed. No action is required.
6202	Utility file system is quiesced but caller does not want to wait.
Action:	The operation returns with a failure.
6203	DSFS address space is terminating, all operations will fail.
Action:	Contact the service representative.
6205	Failure in osi_wait service.
Action:	Contact the service representative.
6206	Task was abended during operation.
Action:	None.
6207	DSFS is shutting down.
Action:	DSFS will not process the requested operation. If this situation persists, contact the service representative.
6208	Admin thread abended.
Action:	An application has issued a pfsctl call (or a user has issued a dsadm command that resulted in a pfsctl call) and the thread running the request in DSFS has abended. Contact the service representative.
6209	Input name is too long.
Action:	Ensure that the input name is not longer than 256 characters. If the name length is valid, contact the service representative.
620A	Task is inactive or was already recovery dispatched or has no recovery stack.
Action:	Contact the service representative.

620B	Had recovery task already, but it did not wake up.
Action: Contact the service representative.	
620C	UIO length is not the size of PC_UNDUB structure.
Action: Contact the service representative.	
620D	Input name contains characters not valid in a data set name.
Action: Ensure that the input name is correct. If the name is valid, contact the service representative.	
620E	This function is not supported.
Action: Contact your service representative.	
620F	Internal failure during creation parameter update.
Action: An internal failure occurred. Contact the service representative.	
6210	Unable to write creation parameters to disk.
Action: Try the operation again and if the issue persists, contact the service representative.	
6211	Base DSFS directories do not allow attributes to be changed.
Action: An attempt to perform a setattr operation on a base DSFS directory was made. DSFS does not directly allow changes to be made to the root directory, or /txt, /bin, /rec by applications.	
6212	An attempt to use SVC 99 to dynamically allocate a data set or member failed.
Action: This error may be expected if a user does not have proper authority to a data set, or another user has the data set allocated in a conflicting mode, or the data set no longer exists.	
6213	An attempt to open a data set or member failed.
Action: This error may be expected if a user does not have proper authority to a data set. Check the system log for any messages that may indicate what caused the error.	
6214	Unable to set creation parameters on this directory type.
Action: Creation parameters are not allowed on root or base or PDS/PDSE directories.	
6215	The CP_REQ contains a bad length, eye catcher, version, or other input.
Action: Correct the CP_REQ fields and try again.	
6216	Unexpected error retrieving or storing data set contents.
Action: This error may be expected if IO errors were reported against the data set. Otherwise, contact the service representative.	
6217	Data format in POSIX file is not able to be stored into the given data set.
Action:	

Use the dsadm fileinfo command to ensure creation parameters are saved for the parent directory.

6225 **Operation failed due to incorrect parent directory type.**

Action:

Parent directory must not be the root or /txt, /bin, or /rec.

6226 **Length of PDS/PDSE member name exceeds allowed maximum or member name contains invalid characters.**

Action:

Ensure that the member name is not longer than the allowed maximum and contains only alphanumeric characters. If both are valid, contact the service representative.

6227 **BPXWDYN call failed.**

Action:

Contact the service representative.

6229 **There is already a data set or member of a PDS or PDSE associated with the target file or directory of the rename.**

Action:

Specify a target file or directory name that is not associated with an existing data set or member.

622A **Data set or member does not exist for the source file or directory of the rename command.**

Action:

Contact the service representative.

622B **Rename of the data set failed.**

Action:

Resolve the problem described in the IDCAMS SYSTEM SERVICES message at the console and issue the command again.

622C **The rename source directory is invalid.**

Action:

The rename source directory must be an HLQ or PDS or PDSE directory.

622D **The target data set name is too long.**

Action:

Specify a data set name of length 44 or less.

622E **The target member name is too long or contains invalid characters.**

Action:

Specify an alphanumeric PDS or PDSE member name of appropriate length.

622F **The target of the operation is a PDS or PDSE directory with open members.**

Action:

DSFS does not support renaming or deleting a PDS or PDSE with open members. Try the operation again when all members of the PDS are closed.

6231 **Operation failed due to incorrect parent directory type.**

Action:

Parent directory must be an HLQ directory.

6232 **A user or application attempted to use an unsupported path directory name.**

Action:

Specify a supported path directory name and try the command again.

6234	FSINFO failed because the utility file system is not mounted.
Action: Retry the command after the utility file system is mounted.	
6235	BPXWDYN returned success, but failed to allocate the data set.
Action: Consult the DSFS documentation and ensure that all necessary creation parameters are assigned to the parent HLQ directory.	
6236	Could not get a list of data sets or PDS members while populating the directory.
Action: Check the system log for any messages associated with the data set. After resolving those issues, try and access the directory again. If the problem persists, contact the service representative.	
623A	Internal errors were encountered while creating the the HLQ directory name cache.
Action: Contact the service representative.	
623B	Utility file system not mounted.
Action: Ensure that the utility file system is mounted. Retry the operation. If it continues to fail, contact the service representative.	
623C	An attempt to save data set creation parameters with RECFM=U attribute on HLQ directories in the /txt or /rec path is not supported.
Action: Saving data set creation parameters with RECFM=U attribute on HLQ directories in /txt or /rec path is not supported. Ensure that the HLQ directory path is /bin or remove the RECFM=U attribute from the data set creation parameters with the dsadm createparm command and try again.	
623D	DSFS cannot dynamically allocate a data set (or member) because the data set (or member) is already dynamically allocated in a conflicting mode in another path.
Action: Wait for the data set or member to be unallocated. Retry the operation. If the problem persists, contact the service representative.	
623E	DSFS cannot enqueue a data set member because the member is already enqueued in a conflicting mode in another path.
Action: Wait for the member enqueue to be released. Retry the operation. If the problem persists, contact the service representative.	
623F	DSFS cannot rename or remove open objects.
Action: Retry the operation when the object is no longer open.	
6240	The limit of in-use data sets has been reached.
Action: Wait for data sets to be unallocated and try the request again. If the problem persists, contact the service representative.	
6241	The utility file system is quiesced.
Action: Try the operation again later. If the problem persists, contact the service representative.	

6242	The dsadm createparm command failed because the HLQ of the high-level qualifier directory name does not match the current user ID.
Action: Issue the dsadm createparm from the correct high-level qualifier directory.	
6243	An attempt to exclusively lock a vnode failed because the vnode is still in use.
Action: Look for message IDFS00159I on the operator console or in the system log. This can indicate DSFS has called slow-running system services. If appropriate, gather diagnostic information and consider a DSFS restart. If the problem persists, contact the service representative.	
625C	A catalog search found that the data set is encrypted, but the UTFS is not encrypted.
Action: If the data set is encrypted, the UTFS must be encrypted in order to access the data set with DSFS.	
6300-637F	An internal error occurred in a DSFS file system subcomponent. A DSFS reason code has the form EDxxxxyy: where xx is the subcomponent identifier of the subcomponent that experienced the problem and yy identifies the location in the subcomponent for the error.
Action: Contact the service representative.	

Appendix A. Accessibility

Accessible publications for this product are offered through [IBM Documentation for z/OS \(www.ibm.com/docs/en/zos\)](http://www.ibm.com/docs/en/zos).

If you experience difficulty with the accessibility of any z/OS documentation see [How to Send Feedback to IBM](#) to leave documentation feedback.

Notices

This information was developed for products and services that are offered in the USA or elsewhere.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
United States of America*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan*

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

This information could include missing, incorrect, or broken hyperlinks. Hyperlinks are maintained in only the HTML plug-in output for IBM Documentation. Use of hyperlinks in other output formats of this information is at your own risk.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Corporation
Site Counsel
2455 South Road*

Poughkeepsie, NY 12601-5400
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

Applicability

These terms and conditions are in addition to any terms of use for the IBM website.

Personal use

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

Commercial use

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or

reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

Rights

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

IBM Online Privacy Statement

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user, or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies that collect each user's name, email address, phone number, or other personally identifiable information for purposes of enhanced user usability and single sign-on configuration. These cookies can be disabled, but disabling them will also eliminate the functionality they enable.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at ibm.com/privacy and IBM's Online Privacy Statement at ibm.com/privacy/details in the section entitled "Cookies, Web Beacons and Other Technologies," and the "IBM Software Products and Software-as-a-Service Privacy Statement" at ibm.com/software/info/product-privacy.

Policy for unsupported hardware

Various z/OS elements, such as DFSMSdfp, JES2, and MVS, contain code that supports specific hardware servers or devices. In some cases, this device-related element support remains in the product even after the hardware devices pass their announced End of Service date. z/OS may continue to service element code; however, it will not provide service related to unsupported hardware devices. Software problems related to these devices will not be accepted for service, and current service activity will cease if a problem is determined to be associated with out-of-support devices. In such cases, fixes will not be issued.

Minimum supported hardware

The minimum supported hardware for z/OS releases identified in z/OS announcements can subsequently change when service for particular servers or devices is withdrawn. Likewise, the levels of other software products supported on a particular release of z/OS are subject to the service support lifecycle of those

products. Therefore, z/OS and its product publications (for example, panels, samples, messages, and product documentation) can include references to hardware and software that is no longer supported.

- For information about software support lifecycle, see: [IBM Lifecycle Support for z/OS \(www.ibm.com/software/support/systemsz/lifecycle\)](http://www.ibm.com/software/support/systemsz/lifecycle)
- For information about currently-supported IBM hardware, contact your IBM representative.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at [Copyright and Trademark information \(www.ibm.com/legal/copytrade.shtml\)](http://www.ibm.com/legal/copytrade.shtml).

UNIX is a registered trademark of The Open Group in the United States and other countries.

Index

Numerics

[6000 85](#)
[6001 85](#)
[6002 85](#)
[6003 85](#)
[6004 85](#)
[6005 85](#)
[6006 85](#)
[6007 85](#)
[6008 85](#)
[6009 85](#)
[600A 85](#)
[600B 86](#)
[600D 86](#)
[6013 86](#)
[6015 86](#)
[6016 86](#)
[6017 86](#)
[6018 86](#)
[601B 86](#)
[601C 86](#)
[601D 86](#)
[601F 86](#)
[6020 86](#)
[6021 86](#)
[6022 87](#)
[6024 87](#)
[6025 87](#)
[6026 87](#)
[6027 87](#)
[6028 87](#)
[6029 87](#)
[602C 87](#)
[602E 87](#)
[602F 87](#)
[6031 87](#)
[6034 87](#)
[6036 87](#)
[6037 87](#)
[6038 88](#)
[6039 88](#)
[603A 88](#)
[603E 88](#)
[603F 88](#)
[6040 88](#)
[6042 88](#)
[6043 88](#)
[6047 88](#)
[6048 88](#)
[6049 88](#)
[604A 88](#)
[604F 88](#)
[6050 89](#)
[6051 89](#)
[6052 89](#)
[6054 89](#)

[6055 89](#)
[6056 89](#)
[6057 89](#)
[6058 89](#)
[605A 89](#)
[605C 89](#)
[605E 89](#)
[6060 89](#)
[6061 89](#)
[6064 90](#)
[6065 90](#)
[6067 90](#)
[6068 90](#)
[6069 90](#)
[606A 90](#)
[606B 90](#)
[606C 90](#)
[606D 90](#)
[606E 90](#)
[606F 90](#)
[6070 90](#)
[6071 90](#)
[6072 90](#)
[6073 90](#)
[6074 91](#)
[6075 91](#)
[6076 91](#)
[6077 91](#)
[6078 91](#)
[6079 91](#)
[607A 91](#)
[607D 91](#)
[607E 91](#)
[607F 91](#)
[6080 91](#)
[6081 91](#)
[6082 91](#)
[6083 91](#)
[6084 92](#)
[6085 92](#)
[6088 92](#)
[6089 92](#)
[608A 92](#)
[608B 92](#)
[608D 92](#)
[608E 92](#)
[608F 92](#)
[6090 92](#)
[6092 92](#)
[6093 92](#)
[6094 92](#)
[6095 92](#)
[6096 93](#)
[6097 93](#)
[6098 93](#)
[6099 93](#)
[609A 93](#)

609B 93	6103 98
609D 93	6104 98
609E 93	6105 98
609F 93	6106 98
60A0 93	6109 98
60A1 93	6116 98
60A2 93	6117 98
60A3 93	6118 98
60A4 93	6119 98
60A5 94	611A 98
60A8 94	611B 98
60A9 94	611C 98
60AB 94	611D 98
60AD 94	611E 99
60AE 94	6120 99
60AF 94	6121 99
60B0 94	6124 99
60B5 94	6127 99
60B6 94	6128 99
60B7 94	6129 99
60B8 94	612A 99
60B9 94	612B 99
60BA 94	612C 99
60BB 95	612D 99
60BC 95	6134 100
60BD 95	6135 100
60BE 95	6136 100
60BF 95	6137 100
60C0 95	6138 100
60C1 95	6139 100
60C3 95	613A 100
60C6 95	613B 100
60C8 95	613C 100
60C9 95	613D 100
60CA 95	613E 100
60CB 95	613F 100
60CC 96	6140 100
60CD 96	6141 101
60CF 96	6142 101
60D0 96	6144 101
60D1 96	6145 101
60D2 96	6146 101
60D3 96	614A 101
60D4 96	614B 101
60D5 96	614C 101
60D6 96	614D 101
60DB 96	614E 101
60DC 96	614F 101
60DD 96	6150 101
60DE 96	6151 101
60DF 97	6152 102
60F0 97	6153 102
60F1 97	6154 102
60F2 97	6155 102
60F3 97	6156 102
60F4 97	6159 102
60FA 97	615A 102
60FB 97	615B 102
60FD 97	615E 102
60FE 97	6160 102
60FF 97	6162 102
6100 97	6163 102
6101 97	6164 103
6102 97	6165 103

[6166 103](#)
[6167 103](#)
[6169 103](#)
[616B 103](#)
[616C 103](#)
[616D 103](#)
[616E 103](#)
[616F 103](#)
[6170 103](#)
[6172 103](#)
[6174 104](#)
[6175 104](#)
[6176 104](#)
[6177 104](#)
[617C 104](#)
[617D 104](#)
[618C 104](#)
[618D 104](#)
[618E 104](#)
[618F 104](#)
[6196 104](#)
[6197 104](#)
[6198 104](#)
[6199 105](#)
[619A 105](#)
[619B 105](#)
[619C 105](#)
[619D 105](#)
[619E 105](#)
[619F 105](#)
[61A0 105](#)
[61A1 105](#)
[61A3 105](#)
[61A4 105](#)
[61A5 105](#)
[61A6 105](#)
[61A7 105](#)
[61A8 105](#)
[61A9 106](#)
[61AB 106](#)
[61AC 106](#)
[61AD 106](#)
[61AE 106](#)
[61AF 106](#)
[61B0 106](#)
[61B1 106](#)
[61B2 106](#)
[61B3 106](#)
[61B4 106](#)
[61BB 106](#)
[61BC 106](#)
[61BD 106](#)
[61BE 107](#)
[61BF 107](#)
[61C0 107](#)
[61C1 107](#)
[61C2 107](#)
[61C3 107](#)
[61C4 107](#)
[61C5 107](#)
[61C6 107](#)
[61C7 107](#)
[61C8 107](#)
[61C9 107](#)

[61CA 107](#)
[61CB 107](#)
[61CC 108](#)
[61CD 108](#)
[61CE 108](#)
[61CF 108](#)
[61D2 108](#)
[61D3 108](#)
[61D4 108](#)
[61D5 108](#)
[61D6 108](#)
[61D7 108](#)
[61D8 108](#)
[61D9 108](#)
[61DA 108](#)
[61DD 109](#)
[61DE 109](#)
[61DF 109](#)
[61E0 109](#)
[61E1 109](#)
[61E3 109](#)
[61E5 109](#)
[61E6 109](#)
[61E7 109](#)
[61E9 109](#)
[61EA 109](#)
[61EB 109](#)
[61EC 109](#)
[61ED 109](#)
[61EE 110](#)
[61EF 110](#)
[61F0 110](#)
[61F1 110](#)
[61F2 110](#)
[61F3 110](#)
[61F7 110](#)
[61F8 110](#)
[61F9 110](#)
[61FA 110](#)
[61FB 110](#)
[61FC 110](#)
[61FD 111](#)
[61FE 111](#)
[61FF 111](#)
[6200 111](#)
[6201 111](#)
[6202 111](#)
[6203 111](#)
[6205 111](#)
[6206 111](#)
[6207 111](#)
[6208 111](#)
[6209 111](#)
[620A 111](#)
[620B 112](#)
[620C 112](#)
[620D 112](#)
[620E 112](#)
[620F 112](#)
[6210 112](#)
[6211 112](#)
[6212 112](#)
[6213 112](#)
[6214 112](#)

[6215 112](#)
[6216 112](#)
[6217 112](#)
[6218 113](#)
[6219 113](#)
[621A 113](#)
[621B 113](#)
[621C 113](#)
[621D 113](#)
[621E 113](#)
[621F 113](#)
[6220 113](#)
[6221 113](#)
[6222 113](#)
[6223 113](#)
[6224 113](#)
[6225 114](#)
[6226 114](#)
[6227 114](#)
[6229 114](#)
[622A 114](#)
[622B 114](#)
[622C 114](#)
[622D 114](#)
[622E 114](#)
[622F 114](#)
[6231 114](#)
[6232 114](#)
[6234 115](#)
[6235 115](#)
[6236 115](#)
[623A 115](#)
[623B 115](#)
[623C 115](#)
[623D 115](#)
[623E 115](#)
[623F 115](#)
[6240 115](#)
[6241 115](#)
[6242 116](#)
[6243 116](#)
[625C 116](#)
[6300 116](#)
[6301 116](#)
[6302 116](#)
[6303 116](#)
[6304 116](#)
[6305 116](#)
[6306 116](#)
[6307 116](#)
[6308 116](#)
[6309 116](#)
[6310 116](#)
[6311 116](#)
[6312 116](#)
[6313 116](#)
[6314 116](#)
[6315 116](#)
[6316 116](#)
[6317 116](#)
[6318 116](#)
[6319 116](#)
[6320 116](#)
[6321 116](#)

[6322 116](#)
[6323 116](#)
[6324 116](#)
[6325 116](#)
[6326 116](#)
[6327 116](#)
[6328 116](#)
[6329 116](#)
[6330 116](#)
[6332 116](#)
[6333 116](#)
[6334 116](#)
[6335 116](#)
[6336 116](#)
[6337 116](#)

A

[accessibility](#)
[contact IBM 117](#)
[assistive technologies 117](#)

C

[contact](#)
[z/OS 117](#)

I

[IDFS000001E 3](#)
[IDFS00002E 3](#)
[IDFS00003I 4](#)
[IDFS00004A 4](#)
[IDFS000053 4](#)
[IDFS00006I 4](#)
[IDFS00007A 5](#)
[IDFS00008A 5](#)
[IDFS00009A 5](#)
[IDFS00010A 6](#)
[IDFS00011A 6](#)
[IDFS00012A 6](#)
[IDFS00013I 7](#)
[IDFS00014A 7](#)
[IDFS00015A 7](#)
[IDFS00016E 8](#)
[IDFS00017I 8](#)
[IDFS00018E 9](#)
[IDFS00019E 9](#)
[IDFS00020I 9](#)
[IDFS00033I 10](#)
[IDFS00034I 10](#)
[IDFS00035I 10](#)
[IDFS00036I 10](#)
[IDFS00037E 10](#)
[IDFS00038E 11](#)
[IDFS00039I 11](#)
[IDFS00040I 11](#)
[IDFS00041A 11](#)
[IDFS00042I 12](#)
[IDFS00043E 12](#)
[IDFS00044I 12](#)
[IDFS00045A 13](#)
[IDFS00046A 13](#)

[IDFS00047A 13](#)
[IDFS00048E 14](#)
[IDFS00049E 14](#)
[IDFS00050E 14](#)
[IDFS00051E 15](#)
[IDFS00052E 15](#)
[IDFS00054E 15](#)
[IDFS00055E 15](#)
[IDFS00056E 16](#)
[IDFS00057E 16](#)
[IDFS00058E 16](#)
[IDFS00062E 16](#)
[IDFS00064I 17](#)
[IDFS00065E 17](#)
[IDFS00066E 17](#)
[IDFS00069E 17](#)
[IDFS00070E 18](#)
[IDFS00071I 18](#)
[IDFS00072A 18](#)
[IDFS00076I 19](#)
[IDFS00077I 19](#)
[IDFS00078I 19](#)
[IDFS00079I 20](#)
[IDFS00080I 20](#)
[IDFS00081I 20](#)
[IDFS00082I 21](#)
[IDFS00083I 21](#)
[IDFS00084I 21](#)
[IDFS00085I 22](#)
[IDFS00086I 22](#)
[IDFS00087E 22](#)
[IDFS00088I 22](#)
[IDFS00089I 23](#)
[IDFS00090I 23](#)
[IDFS00091E 23](#)
[IDFS00093E 24](#)
[IDFS00094E 24](#)
[IDFS00095I 25](#)
[IDFS00096I 25](#)
[IDFS00100E 25](#)
[IDFS00101E 25](#)
[IDFS00103I 26](#)
[IDFS00104I 26](#)
[IDFS00105E 26](#)
[IDFS00106E 27](#)
[IDFS00107I 27](#)
[IDFS00108A 27](#)
[IDFS00110I 28](#)
[IDFS00111E 28](#)
[IDFS00112A 28](#)
[IDFS00113E 29](#)
[IDFS00114E 29](#)
[IDFS00115E 29](#)
[IDFS00116E 30](#)
[IDFS00117E 30](#)
[IDFS00118I 30](#)
[IDFS00120E 30](#)
[IDFS00121I 31](#)
[IDFS00123I 31](#)
[IDFS00129E 32](#)
[IDFS00130E 32](#)
[IDFS00131E 32](#)
[IDFS00134E 33](#)
[IDFS00137E 33](#)

[IDFS00138I 33](#)
[IDFS00139I 34](#)
[IDFS00143E 34](#)
[IDFS00145I 34](#)
[IDFS00146I 35](#)
[IDFS00148E 35](#)
[IDFS00149E 35](#)
[IDFS00150E 35](#)
[IDFS00151E 36](#)
[IDFS00152E 36](#)
[IDFS00153I 36](#)
[IDFS00156E 37](#)
[IDFS00158E 37](#)
[IDFS00159I 38](#)
[IDFS00160I 39](#)
[IDFS00161I 39](#)
[IDFS00162A 40](#)
[IDFS00164I 40](#)
[IDFS00165I 40](#)
[IDFS00166I 41](#)
[IDFS00167E 41](#)
[IDFS00167I 41](#)
[IDFS00171E 42](#)
[IDFS00172E 42](#)
[IDFS00173E 42](#)
[IDFS00174E 42](#)
[IDFS00175E 43](#)
[IDFS00176E 43](#)
[IDFS00177I 43](#)
[IDFS00179I 44](#)
[IDFS00180E 44](#)
[IDFS00181I 44](#)
[IDFS00182E 45](#)
[IDFS00183I 45](#)
[IDFS00184E 45](#)
[IDFS00185E 45](#)
[IDFS00188I 46](#)
[IDFS00189I 46](#)
[IDFS00190I 46](#)
[IDFS00191E 46](#)
[IDFS00197I 47](#)
[IDFS00198I 47](#)
[IDFS00200I 47](#)
[IDFS00201I 47](#)
[IDFS00202I 48](#)
[IDFS00203I 48](#)
[IDFS00204I 48](#)
[IDFS00206E 49](#)
[IDFS00212E 49](#)
[IDFS00222A 49](#)
[IDFS00223I 50](#)
[IDFS00224A 51](#)
[IDFS00227I 51](#)
[IDFS00228E 52](#)
[IDFS00229E 52](#)
[IDFS00231I 52](#)
[IDFS00233E 53](#)
[IDFS00234E 53](#)
[IDFS00235I 53](#)
[IDFS00236I 54](#)
[IDFS00238E 54](#)
[IDFS00239I 55](#)
[IDFS00240E 55](#)
[IDFS00242E 56](#)

[IDFS00243E 56](#)
[IDFS00244E 56](#)
[IDFS00248I 57](#)
[IDFS00255E 57](#)
[IDFS00256E 57](#)
[IDFS00260I 58](#)
[IDFS00261I 58](#)
[IDFS00262I 58](#)
[IDFS00263I 58](#)
[IDFS00264I 59](#)
[IDFS00269I 59](#)
[IDFS00271E 59](#)
[IDFS00272E 59](#)
[IDFS00273E 60](#)
[IDFS00274E 60](#)
[IDFS00279A 60](#)
[IDFS00280A 61](#)
[IDFS00281E 61](#)
[IDFS00282I 61](#)
[IDFS00283E 62](#)
[IDFS00284E 62](#)
[IDFS00285E 62](#)
[IDFS00286E 63](#)
[IDFS00287E 63](#)
[IDFS00288E 63](#)
[IDFS00289E 64](#)
[IDFS00290E 64](#)
[IDFS00292E 64](#)
[IDFS00293I 65](#)
[IDFS00294I 65](#)
[IDFS00295I 65](#)
[IDFS00296I 65](#)
[IDFS00297I 66](#)
[IDFS00298E 66](#)
[IDFS00299E 66](#)
[IDFS00300E 67](#)
[IDFS00301E 67](#)
[IDFS00302I 67](#)
[IDFS00303E 67](#)
[IDFS00305I 68](#)
[IDFS00306I 68](#)
[IDFS00307I 68](#)
[IDFS00308E 68](#)
[IDFS00313I 69](#)
[IDFS00319I 69](#)
[IDFS00320I 69](#)
[IDFS00324E 70](#)
[IDFS00325E 70](#)
[IDFS00326I 71](#)
[IDFS00327I 71](#)
[IDFS00328E 71](#)
[IDFS00329E 71](#)
[IDFS00330E 71](#)
[IDFS00331E 72](#)
[IDFS00333E 72](#)
[IDFS00334E 72](#)
[IDFS00335E 73](#)
[IDFS00336E 73](#)
[IDFS00337E 74](#)
[IDFS00339E 74](#)
[IDFS00340E 74](#)
[IDFS00341E 75](#)
[IDFS00342E 75](#)
[IDFS00343E 75](#)

[IDFS00344E 76](#)
[IDFS00345E 76](#)
[IDFS00346E 77](#)
[IDFS00347I 77](#)
[IDFS00348I 77](#)
[IDFS00349E 78](#)
[IDFS00351A 78](#)
[IDFS00352I 78](#)
[IDFS00353I 79](#)
[IDFS00354E 79](#)
[IDFS00355E 79](#)
[IDFS00356E 80](#)
[IDFS00357E 80](#)
[IDFS00358E 80](#)
[IDFS00359E 81](#)
[IDFS00360E 81](#)
[IDFS00361E 81](#)
[IDFS00362E 82](#)
[IDFS00363E 82](#)
[IDFS00364E 82](#)
[IDFS00365E 82](#)

K

keyboard
 navigation [117](#)
 PF keys [117](#)
 shortcut keys [117](#)

M

messages
 z/OS Data Set File System Messages and Codes
 [ix](#)

N

navigation
 keyboard [117](#)

R

reason codes [85](#)

S

severity levels [1](#)
shortcut keys [117](#)
slip trap
 diagnosis data
 setting [2](#)
 setting [2](#)

U

user interface
 ISPF [117](#)
 TSO/E [117](#)

Z

z/OS Data Set File System Messages and
Codes

[messages ix](#)

[messages, changed ix](#)

[messages, new ix](#)

[messages, no longer issued ix](#)



Product Number: 5655-ZOS

GI13-5604-70

